



Powering Business Worldwide

## KVM Switch - 4-Port Desktop KVM Switch (USB)

MODEL NUMBER: B006-004-R



### Highlights

- USB Connections on both Console and Server side
- P758-Series KVM Cable kit required to connect to a computer
- Push Button switching on the front of the unit
- Built-in 2-Port USB hub shares two USB peripherals between attached systems
- OS independent operation - use with PCs or MACs

### Package Includes

- B006-004-R 4-port USB KVM Switch
- Instruction manual with warranty information

### Description

Tripp Lite's 4-port Desktop USB KVM Switch is the optimal solution for controlling up to 4 USB computers from one keyboard, mouse, and monitor. It features keyboard and mouse emulation for error-free boot-ups and works on all operating systems. This device also supports 180MHz video resolutions up to 1920 x 1440 pixels without any noticeable degradation. It features a compact design that does not require external power, software, or complicated set-up procedures.

### Features

- Control up to 4 USB computers from a single keyboard, mouse and monitor
- Console Ports: HD15 Female (Monitor) and 2 USB A Female (Keyboard/Mouse)
- Computer Ports: 4 HD15 Male (Monitor) and 4 USB B Female (Dual Keyboard/Mouse)
- Includes 2 USB A Female ports for sharing of USB peripherals between connected computers
- 2 LEDs per port; one indicates when the computer is connected & on, the other indicates when the computer has been selected
- Supports 180MHz video resolutions up to 1920 x 1440
- Supports VGA, SVGA, or Multisync monitors
- Does not require external power, software, or complicated set-up procedures
- Select a computer via front panel push-buttons
- Includes autoscan feature
- Keyboard and mouse emulation for dependable computer boot-up
- Compatible with all operating systems
- Compatible with most mice; including scroll mice

## Specifications

| OVERVIEW |              |
|----------|--------------|
| UPC Code | 037332014962 |
| Console  | No           |



Powering Business Worldwide

|                                      |                       |
|--------------------------------------|-----------------------|
| Max CPU                              | 4                     |
| Product Rear View                    | B006-004-R-rear.pdf   |
| <b>CONNECTIONS</b>                   |                       |
| Number of Ports                      | 4                     |
| Computer/Server Ports - Port 1       | HD15 (Male)           |
| Computer/Server Ports - Port 2       | USB B (Female)        |
| PC/Server Connections                | USB                   |
| <b>PHYSICAL</b>                      |                       |
| LCD Monitor (cm)                     | Not Applicable        |
| LCD Monitor (in.)                    | Not Applicable        |
| Shipping Dimensions (hwd / in.)      | 4.00 x 13.00 x 8.50   |
| Shipping Dimensions (hwd / cm)       | 10.16 x 33.02 x 21.59 |
| Shipping Weight (lbs.)               | 3.50                  |
| Shipping Weight (kg)                 | 1.59                  |
| Unit Dimensions (hwd / in.)          | 2.250 x 9.000 x 6.250 |
| Unit Weight (lbs.)                   | 3                     |
| Unit Weight (kg)                     | 1.36                  |
| <b>ENVIRONMENTAL</b>                 |                       |
| BTUs                                 | 50Hz, 2.7 / 60Hz, 2.4 |
| <b>COMMUNICATIONS</b>                |                       |
| Port Control                         | Push Buttons          |
| IP Remote Access                     | No                    |
| <b>FEATURES &amp; SPECIFICATIONS</b> |                       |
| Number of Users                      | 1                     |

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2024 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.