# High Performance BGA Cooling Solutions w/ Thermal Tape Attachment\*

### DIGI-KEY PART # ATS1231-ND


ATS PART # ATS-54190R-C2-R0


#### Features & Benefits

High aspect ratio, straight fin heat sinks that are ideal for compact PCB environments

Designed specifically for BGAs and other surface mount packages

Comes preassembled with high performance thermal interface material





# Thermal Performance Table

AIR VELOCITY		THERMAL RESISTANCE		
FT/MIN	M/S	°C/W (UNDUCTED)	°C/W (DUCTED)	
200	1.0	8.4	5.3	
300	1.5	6.8		
400	2.0	5.9		
500	2.5	5.3		
600	3.0	4.9		
700	3.5	4.5		
800	4.0	4.3		

## **Product Details**<sup>†</sup>

DIMENSION A	DIMENSION B	DIMENSION C <sup>®</sup>	DIMENSION D	TIM <sup>‡</sup>	FINISH
19	19	19.5	N/A	C675	BLACK-ANODIZED

For further technical information, please contact Advanced Thermal Solutions, Inc. at **1-781-769-2800** or **www.qats.com** 

\* RoHS Compliant

‡ TIM = Thermal Interface Material

† Dimensions are measured in millimeters

Dimensions A & B refer to component size
Dimension C = the height of the heat sink of

§ Dimension C = the height of the heat sink shown above and does not include the height of the attachment method ATS ADVANCED THERMAL SOLUTIONS, INC. Innovations in Thermal Management®



To place an order, please visit www.digikey.com