


## 8-Channel EMI-Filter with ESD-Protection



### FEATURES

- Ultra compact LLP3313-17L package
- Low package profile of 0.6 mm
- 8-channel EMI-filter
- Low leakage current
- Line resistance  $R_S = 100 \Omega$
- Typical cut off frequency  $f_{3dB} = 130 \text{ MHz}$
- ESD-protection acc. IEC 61000-4-2  
 $\pm 18 \text{ kV}$  contact discharge  
 $\pm 25 \text{ kV}$  air discharge
- e4 - precious metal (e.g. Ag, Au, NiPd, NiPdAu) (no Sn)
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)



**RoHS**  
COMPLIANT  
HALOGEN  
**FREE**  
**GREEN**  
(5-2008)

### MARKING (example only)



Dot = pin 1 marking  
Y = type code (see table below)  
XX = date code

### DESIGN SUPPORT TOOLS

[click logo to get started](#)


### ORDERING INFORMATION

| DEVICE NAME  | ORDERING CODE     | TAPED UNITS PER REEL<br>(8 mm TAPE ON 7" REEL) | MINIMUM ORDER QUANTITY |
|--------------|-------------------|------------------------------------------------|------------------------|
| VEMI85AB-HGK | VEMI85AB-HGK-GS08 | 3000                                           | 15 000                 |

### PACKAGE DATA



| DEVICE NAME  | PACKAGE NAME | TYPE CODE | WEIGHT | MOLDING COMPOUND<br>FLAMMABILITY RATING | MOISTURE<br>SENSITIVITY LEVEL        | SOLDERING CONDITIONS         |
|--------------|--------------|-----------|--------|-----------------------------------------|--------------------------------------|------------------------------|
| VEMI85AB-HGK | LLP3313-17L  | 9U        | 7.4 mg | UL 94 V-0                               | MSL level 1<br>(according J-STD-020) | Peak temperature max. 260 °C |

### ABSOLUTE MAXIMUM RATINGS

| PARAMETER             | TEST CONDITIONS                                                                      | SYMBOL    | VALUE       | UNIT |
|-----------------------|--------------------------------------------------------------------------------------|-----------|-------------|------|
| Peak pulse current    | All I/O pin to pin 17; acc. IEC 61000-4-5;<br>$t_p = 8/20 \mu\text{s}$ ; single shot | $I_{PPM}$ | 4           | A    |
| ESD immunity          | Contact discharge acc. IEC 61000-4-2; 10 pulses                                      | $V_{ESD}$ | $\pm 18$    | kV   |
|                       | Air discharge acc. IEC 61000-4-2; 10 pulses                                          |           | $\pm 25$    |      |
| Operating temperature | Junction temperature                                                                 | $T_J$     | -40 to +125 | °C   |
| Storage temperature   |                                                                                      | $T_{STG}$ | -55 to +150 | °C   |

## APPLICATION NOTE

With the VEMI85AB-HGK 8 different signal or data lines can be filtered and clamped to ground. Due to the different clamping levels in forward and reverse direction the clamping behaviour is Bidirectional and Asymmetric (BiAs).




20389

The 8 independent EMI-filter are placed between

- pin 1 and pin 16,
- pin 2 and pin 15,
- pin 3 and pin 14,
- pin 4 and pin 13,
- pin 5 and pin 12,
- pin 6 and pin 11,
- pin 7 and pin 10 and
- pin 8 and pin 9.

They all are connected to a common ground pin 17 on the backside of the package.



The circuit diagram of one EMI-filter-channel shows two identical Z-diodes at the input to ground and the output to ground. These Z-diodes are characterized by the breakthrough voltage level ( $V_{BR}$ ) and the diode capacitance ( $C_D$ ). Below the breakthrough voltage level the Z-diodes can be considered as capacitors. Together with these capacitors and the line resistance  $R_S$  between input and output the device works as a low pass filter. Low frequency signals ( $f < f_{3dB}$ ) pass the filter while high frequency signals ( $f > f_{3dB}$ ) will be shorted to ground through the diode capacitances  $C_D$ .









Each filter is symmetrical so that both ports can be used as input or output.


**ELECTRICAL CHARACTERISTICS** All inputs (pin 1, 2, 3, 4, 5, 6, 7, and 8) to ground (pin 17)  
 ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified)


| PARAMETER                  | TEST CONDITIONS/REMARKS                                                                              | SYMBOL        | MIN. | TYP. | MAX. | UNIT          |
|----------------------------|------------------------------------------------------------------------------------------------------|---------------|------|------|------|---------------|
| Protection paths           | Number of channels which can be protected                                                            | $N_{channel}$ | -    | -    | 8    | channel       |
| Reverse stand off voltage  | Max. reverse working voltage                                                                         | $V_{RWM}$     | -    | -    | 5    | V             |
| Reverse voltage            | at $I_R = 1\text{ }\mu\text{A}$                                                                      | $V_R$         | 5    | -    | -    | V             |
| Reverse current            | at $V_R = V_{RWM}$                                                                                   | $I_R$         | -    | 0.25 | 1    | $\mu\text{A}$ |
| Reverse break down voltage | at $I_R = 1\text{ mA}$                                                                               | $V_{BR}$      | 6    | 6.8  | -    | V             |
| Pos. clamping voltage      | at $I_{PP} = 1\text{ A}$ applied at the input, measured at the output; acc. IEC 61000-4-5            | $V_{C-out}$   | -    | -    | 7    | V             |
|                            | at $I_{PP} = I_{PPM} = 4\text{ A}$ applied at the input, measured at the output; acc. IEC 61000-4-5  | $V_{C-out}$   | -    | -    | 8    | V             |
| Neg. clamping voltage      | at $I_{PP} = -1\text{ A}$ applied at the input, measured at the output; acc. IEC 61000-4-5           | $V_{C-out}$   | -1.4 | -    | -    | V             |
|                            | at $I_{PP} = I_{PPM} = -4\text{ A}$ applied at the input, measured at the output; acc. IEC 61000-4-5 | $V_{C-out}$   | -1.6 | -    | -    | V             |
| Input capacitance          | at $V_R = 0\text{ V}$ ; $f = 1\text{ MHz}$                                                           | $C_{IN}$      | -    | 40   | 45   | pF            |
|                            | at $V_R = 2.5\text{ V}$ ; $f = 1\text{ MHz}$                                                         | $C_{IN}$      | -    | 24   | 28   | pF            |
| ESD-clamping voltage       | at $\pm 18\text{ kV}$ ESD-pulse acc. IEC 61000-4-2                                                   | $V_{CESD}$    | -    | 7.5  | -    | V             |
| Line resistance            | Measured between input and output;<br>$I_S = 10\text{ mA}$                                           | $R_S$         | 90   | 100  | 110  | $\Omega$      |
| Cut-off frequency          | $V_{IN} = 0\text{ V}$ ; measured in a $50\text{ }\Omega$ system                                      | $f_{3dB}$     | -    | 130  | -    | MHz           |

**TYPICAL CHARACTERISTICS** ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified)

 Fig. 1 - ESD Discharge Current Wave Form  
 acc. IEC 61000-4-2 (330  $\Omega$ /150 pF)

 Fig. 2 - 8/20  $\mu\text{s}$  Peak Pulse Current Wave Form  
 acc. IEC 61000-4-5


Fig. 3 - Typical Forward Current  $I_F$  vs. Forward Voltage  $V_F$ 

Fig. 6 - Typical Input Capacitance  $C_{IN}$  vs. Input Voltage  $V_{IN}$ 

Fig. 4 - Typical Reverse Voltage  $V_R$  vs. Reverse Current  $I_R$ 

Fig. 7 - Typical Small Signal Transmission ( $S_{21}$ ) at  $Z_O = 50 \Omega$ 

Fig. 5 - Typical Peak Clamping Voltage  $V_C$  vs. Peak Pulse Current  $I_{PP}$

**PACKAGE DIMENSIONS** in millimeters (inches): **LLP3313-17L**


Foot print recommendation:



Document no.: S8-V-3906.04-003 (4)  
Created - Date: 28. August 2006  
Rev. 1 - Date: 27. May 2008  
20391



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.