

# Power It! 10-Outlet Power Strip, 15 ft. (4.57 m) Cord

MODEL NUMBER: TLM1015NC



### Highlights

- 10 outlets spaced to accommodate transformers
- Illuminated on/off switch with cover
- 15-amp circuit breaker
- 15-ft. (4.57 m) power cord
- Heavy-duty metal case
- Keyhole slots on removable mounting brackets

### Package Includes

- TLM1015NC power strip
- Warranty information
- Instruction manual

### Description

The Power It!® TLM1015NC power strip offers reliable, convenient and cost-effective power distribution for appliances, power tools, lighting and other electrical equipment. Includes 10 NEMA 5-15R outlets spaced to accommodate transformers, 15-foot (4.6 meters) AC power cord and keyhole slots on removable mounting brackets. Multi-outlet strip reduces cable clutter and enables the connection of multiple electrical devices to a single AC wall socket. Features heavy-duty metal case to stand up to the most demanding environments, illuminated power switch with transparent cover to prevent accidental shutoff and 15A integrated circuit breaker to prevent dangerous overloads.

### Features

- Multi-outlet power strip offers reliable, convenient and cost-effective power distribution for appliances, power tools, lighting and other electrical equipment
- Includes 10 NEMA 5-15R outlets spaced to accommodate transformers
- Illuminated on/off switch provides one-touch power control for connected equipment
- Transparent switch cover snaps tight to prevent accidental shutoff
- Convenient keyhole slots on removable brackets provide secure mounting options for a wide variety of surfaces and applications
- 15A power handling capacity with integrated circuit breaker
- 120V AC, 50/60Hz electrical compatibility
- 15-ft. (4.57 m) AC power cord
- Heavy-duty metal case provides maximum safety and durability
- UL certification

## Specifications

| OVERVIEW |              |
|----------|--------------|
| UPC Code | 037332136107 |
| INPUT    |              |



Powering Business Worldwide



|   |  |
|---|--|
| Nominal Input Voltage(s) Supported                | 120V AC  |
| Recommended Electrical Service                    | 15A 120V   |
| Input Cord Gauge Type                             | 14 gauge; SJT  |
| Voltage Compatibility (VAC)                       | 120  |
| Input Plug Type                                   | NEMA 5-15P   |
| Input Cord Length (ft.)                           | 15   |
| Right-Angle Plug                                  | No   |
| Input Cord Length (m)                             | 4.57   |
| Integrated Cord Clip                              | No   |
| <b>OUTPUT</b>                                     |  |
| Frequency Compatibility                           | 50 / 60 Hz   |
| Output Receptacles                                | (10) 5-15R   |
| Circuit Breaker (amps)                            | 15   |
| Overload Protection                               | 15A circuit breaker  |
| Transformer Accommodation                         | (5) Yes  |
| Outlet Orientation                                | 10 outlets arranged in 2 rows and spaced to accommodate transformers                         |
| Right-Angle Outlets                               | No   |
| <b>USER INTERFACE, ALERTS &amp; CONTROLS</b>      |  |
| Switches  | Lighted 2 position switch controls power to all outlets                                      |
| Locking Switch Cover                              | Transparent switch cover snaps tight to prevent accidental shutoff                           |
| <b>PHYSICAL</b>                                   |  |
| Color   | Light Gray   |
| Material of Construction                          | Metal  |
| Power Cord Color                                  | Light Gray   |
| Housing Color                                     | Light Gray   |
| Included Mounting Accessories                     | Keyhole slots on removable mounting brackets   |
| Mounting Holes or Slots                           | Yes  |
| Slot or Hole Mount Measurement (Center to Center) | Distance between end tabs = 462.30mm   |
| Outlets Measurement (Center to Center)            | Distance between horizontal outlets = 2.81 in.; Distance between vertical outlets = 1.53 in. |
| Receptacle Color                                  | Light gray   |
| Shipping Dimensions (hwd / in.)                   | 2.60 x 9.10 x 20.20  |
| Shipping Dimensions (hwd / cm)                    | 6.60 x 23.11 x 51.31   |
| Shipping Weight (lbs.)                            | 5.10   |



Powering Business Worldwide



|                                      |                                |
|--------------------------------------|--------------------------------|
| Shipping Weight (kg)                 | 2.31                           |
| Unit Dimensions (hwd / in.)          | 2.250 x 17.500 x 4.000         |
| Unit Dimensions (hwd / cm)           | 44.5 x 10.2 x 5.7              |
| Unit Weight (lbs.)                   | 4.6                            |
| Unit Weight (kg)                     | 2.09                           |
| Mounting Details                     | Includes flanges               |
| <b>FEATURES &amp; SPECIFICATIONS</b> |                                |
| Antimicrobial                        | No                             |
| Built-In Circuit Breaker             | Yes                            |
| <b>STANDARDS &amp; COMPLIANCE</b>    |                                |
| Product Certifications               | cUL Listed; UL 1363; UL Listed |
| Product Compliance                   | RoHS                           |
| <b>WARRANTY &amp; SUPPORT</b>        |                                |
| Product Warranty Period (Worldwide)  | Lifetime limited warranty      |

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2024 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.