

5.8kW 200-240V Single-Phase Basic PDU - 16 C13 & 4 C19 Outlets, L6-30P Input, 15 ft. (4.6 m) Cord, 1U Rack-Mount

MODEL NUMBER: PDU1230



Delivers 200–240V single-phase AC power to multiple loads from a utility outlet, generator or UPS system in a data center or network closet.

Description

The PDU1230 4.8/5.8kW Single-Phase 200-240V Basic PDU is the perfect no-frills unit for networking, telecom, security, audio/video and sound reinforcement applications. Perfectly suited for high-density IT environments, the PDU1230 features 20 total outlets—12 rear C13, four front C13 and four front C19. The NEMA L6-30P input plug with long 15-foot (4.6 meters) cord connects to your facility's compatible AC power source, generator or protected UPS to distribute power to connected equipment.

The switchless design prevents an accidental shutdown, which could lead to costly downtime. Built-in circuit breakers protect connected equipment from dangerous overloads. The reversible all-metal housing mounts in 1U of space in EIA-standard 19-inch racks, as well as on a wall or workbench or under a counter. With a compatible rack and a PDUSIDEBRKT accessory (sold separately), you can adapt the PDU1230 for vertical 0U rack-mounting.

Features

Single-Phase 200–240V PDU Distributes Network-Grade Power to Multiple Loads

This basic PDU is an ideal no-frills unit for networking, telecom, security, audio/video and sound reinforcement applications. Recommended for high-density IT environments, the PDU1230 features 20 outlets: 12 C13 outlets in the rear and four C13 and four C19 outlets in front. A 15-foot (4.6-meter) cord with NEMA L6-30P input plug connects to your facility's compatible AC power source, generator or protected UPS system to distribute power to connected loads.

Up-to-Date Safety Features Protect Your Vital Equipment

The switchless design helps prevent an accidental shutdown, which could lead to costly downtime. Built-in circuit breakers protect connected equipment from dangerous overloads.

Versatile Installation Options Give You Plenty of Choices

The reversible all-metal housing comes with mounting brackets for installation in 1U of space in an EIA-standard 19-inch rack, as well as on a wall or workbench or under a counter. With the optional PDUSIDEBRKT accessory (sold separately), you can also adapt the PDU1230 for 0U vertical rack-mounting.

Specifications

Highlights

- Ideal no-frills PDU for telecom, security, AV and sound reinforcement applications
- 16 C13 and 4 C19 outlets distribute AC power to connected equipment
- Switchless design helps prevent accidental shutdowns that can lead to costly downtime
- Long 15 ft. cord with NEMA L6-30P single-phase input connects to AC power source
- Flexible installation options include 1U and 0U rack, under counter and on wall

Package Includes

- PDU1230 5.8kW 200–240V Single-Phase Basic PDU
- Rack-mounting hardware
- Owner's manual

| OVERVIEW | |
|--------------------------------------|--|
| UPC Code | 037332122261 |
| PDU Type | Basic |
| INPUT | |
| Input Phase | Single-Phase |
| PDU Input Voltage | 200; 208; 220; 230; 240 |
| Recommended Electrical Service | Single-phase 30A 200-240V service |
| Maximum Input Amps | 24 |
| Maximum Input Amps Details | Agency de-rated to 24A continuous |
| PDU Plug Type | NEMA L6-30P |
| Input Cord Length (ft.) | 15 |
| Input Cord Length (m) | 4.57 |
| OUTPUT | |
| Output Capacity (kW) | 5.8 |
| Output Capacity Details | 5.8kW (240V), 5.5kW (230V), 5.3kW (220V), 5kW (208V), 4.8kW (200V) total capacity / 30A max (Agency de-rated to 24A); 15A max per breakered C19 outlet bank; 12A max per breakered C13 outlet bank |
| Frequency Compatibility | 50 / 60 Hz |
| Output Receptacles | (16) C13; (4) C19 |
| Output Nominal Voltage | 200-240V |
| Overload Protection | Four 10A breakers protect 4 C13 outlets each; 4 15A breakers protect 1 C19 outlet each |
| USER INTERFACE, ALERTS & CONTROLS | |
| Switches | No power switch |
| SURGE / NOISE SUPPRESSION | |
| Automatic Shut-Off | No |
| PHYSICAL | |
| Material of Construction | Metal |
| Form Factors Supported | 1U rackmount, 0U vertical rackmount, wall-mount and undercounter installation supported |
| Minimum Required Rack Depth (cm) | 22.10 |
| Minimum Required Rack Depth (inches) | 8.7 |
| PDU Form Factor | Horizontal (1U) |
| Shipping Dimensions (hwd / in.) | 11.00 x 2.90 x 20.20 |
| Shipping Dimensions (hwd / cm) | 27.94 x 7.37 x 51.31 |



Powering Business Worldwide



| | |
|--------------------------------------|--|
| Shipping Weight (lbs.) | 8.20 |
| Shipping Weight (kg) | 3.72 |
| Unit Dimensions (hwd / in.) | 1.750 x 17.500 x 5.200 |
| Unit Dimensions (hwd / cm) | 4.5 x 44.5 x 13.2 |
| Unit Weight (lbs.) | 7.5 |
| Unit Weight (kg) | 3.40 |
| ENVIRONMENTAL | |
| Operating Temperature Range | 32° to 104°F (0° to 40°C) |
| Storage Temperature Range | -22° to 122°F (-30° to 50°C) |
| Relative Humidity | 5% to 95% non-condensing |
| Operating Elevation | 0-10000 ft. (0-3000 m) |
| FEATURES & SPECIFICATIONS | |
| Grounding | Grounding lug |
| STANDARDS & COMPLIANCE | |
| Product Certifications | RETIE (Colombia); CAN/CSA-C22.2 No. 62368-1 (Canada); NOM (Mexico); UL 62368-1 |
| Product Compliance | RoHS; Trade Agreements Act (TAA) |
| WARRANTY & SUPPORT | |
| Product Warranty Period (Worldwide) | 5-year limited warranty |

1000 Eaton Boulevard
 Cleveland, OH 44122
 United States
<https://tripplite.eaton.com>

© 2024 Eaton. All Rights Reserved.
 Eaton is a registered trademark. All other trademarks
 are the property of their respective owners.