




Made in the
United States of America



- A. Black ABS plastic cap.
- B. 300 series stainless steel backplate (0.015" thick).
- C. Two 4mm snap studs machined from 300 series stainless steel. Fits to 4mm spring loaded medical type socket. Coil cord disengages from snap with 1-5 lbs. of perpendicular force. Compatible with [Desco Dual-Wire Coil Cords](#) ONLY (not including MagSnap® or MagSnap360™ products).
- D. Premium metal expansion wrist strap. Inside links are constructed of 300 Series Stainless Steel. Width of links is 0.630".
- E. .002" polyphenylsulfone sheet is laminated to each link before assembly. Provides >5,000 volt RMS insulation per ASTM D149. Will not flake or peel.
- F. Black ABS plastic insulator separates band into halves.
- G. Underwriters' Laboratory listed 90P1C.
Meets required limits of ANSI/ESD S20.20 and requirements of ANSI/ESD S1.1.

ITEM	BAND SIZE	CIRCUMEFERENCE		WIDTH
		MIN	MAX	
19844	Small	5.5" (140mm)	9" (229mm)	0.630"
19842	Medium	6" (152mm)	11" (279mm)	0.630"
19840	Large	7" (178mm)	12" (305mm)	0.630"

Specifications and procedures subject to change without notice.
Unless otherwise noted, tolerance $\pm 10\%$
*U.S. Patents 6,052,053 and 6,205,408

See Drawing [09163](#) for details on Jewel® Coil Cords

Jewel® Premium Metal Expansion Dual-Wire Wrist Strap, 4mm

DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710 WEB SITE: [Desco.com](#)
PHONE (909) 627-8178 FAX (909) 627-7449

DESCO EAST: ONE COLGATE WAY, CANTON, MA 02021-1407
PHONE (781) 821-8370 FAX (781) 575-0172

DRAWING NUMBER
09165

DATE:
November
2016

DESCO