



Rating	20A 125VAC 10A 25VAC	Mounting Hole			Circuit Diagram
	16A 125VAC 3/4HP				
	10A 277VAC 3/4HP				
	21A 14VDC				
Contact Resistance	50m ohm Max.				
Insulation Resistance	DC 500V 100M ohm Min.				
Dielectric Strength	AC 1500V 1 minute				
Operation Temperature	-20°~+85°				
Switch Function	2P SPST (ON)-OFF	Thickness(mm)	X(mm)	Y(mm)	
		0.75~1.25	21.2±0.1	36.6 ^{+0.2} ₋₀	
		1.25~2.0		36.8 ^{+0.2} ₋₀	
		2.0~3.0		37.0 ^{+0.2} ₋₀	

()= Momentary Function






* MATERIAL:

Frame: Nylon#66, Black


Actuator: Nylon#66 with 33%GF, Black

Printed: None

Water proof and dust proof to fit IP-56



DATE CODE



RoHS Compliant

CW INDUSTRIES
Southampton, Pa. 18966
Tel 215.355.7080/www.cwind.com

Date Drawn: 5/18/10

Rev. 0

Unit: mm

Checked By: EJP

Title:

ROCKER SWITCH

CW P/N:

GRB260N601BBNN