




CUSTOMER TERMINAL	RoHS	LEAD(Pb)-FREE
Sn96%, Ag4%	Yes	Yes

more than you expect



Customer to tie terminals 3+9
Internally on PC board.



ELECTRICAL SPECIFICATIONS @ 25°C unless otherwise noted:

PARAMETER	TEST CONDITIONS	VALUE
D.C. RESISTANCE	4-8	tie(3+9), @20°C
D.C. RESISTANCE	7-6	@20°C
D.C. RESISTANCE	FL1-FL2	@20°C
INDUCTANCE	4-8	tie(3+9), 10kHz, 100mVAC, Ls
SATURATION CURRENT		20% rolloff from initial
LEAKAGE INDUCTANCE	4-8	tie(3+9, FL1+FL2), 100kHz, 100mVAC, Ls
DIELECTRIC	4-FL1	tie(3+9, 4+7), 4500VAC, 1 second
URNS RATIO	(4-8):(7-6), tie(3+9)	7:1, ±2%
URNS RATIO	(4-8):(FL1-FL2), tie(3+9)	5.33:1, ±2%
URNS RATIO	(4-9):(3-8)	1:1, ±2%

GENERAL SPECIFICATIONS:

OPERATING TEMPERATURE RANGE: -40°C to +125°C including temp rise.

Designed to comply with the following requirements as defined by IEC61558-2-17:
- Reinforced insulation for a primary circuit at a working voltage of 400VDC.

Wire insulation & RoHS status not affected by wire color.
Wire insulation color may vary depending on availability.

REV.	DATE	Packaging Specifications Method: Tape & Reel PKG-0358 www.we-online.com/midcom	CONVENTION PLACEMENT	Tolerances unless otherwise specified: Angles: ±1° Fractions: ±1/64 Decimals: ±.005 [.13] Footprint: ±.005 [.13]	DRAWING TITLE TRANSFORMER	PART NO. 750311620
6A	11/10	SEE REVISION SHEET FOR REVISION LEVEL		This drawing is dual dimensioned. Dimensions in brackets are in millimeters.	eiSos p/n: 750311620	SPECIFICATION SHEET 1 OF 1

