





PRODUCT SPECIFICATION

DATE: 11/18/2003



COSMO ELECTRONICS CORPORATION	SOLID STATE RELAY-MOSFET OUTPUT KAQW212S	NO. 62M20006	REV.
		SHEET 1 OF 7	1

- OUTSIDE DIMENSION :



Unit:mm
Tolerance: ± 0.2 mm

- Turn on/Turn off time



Absolute Maximum Ratings ($T_A=25^\circ C$)

Emitter (Input)

Reverse Voltage 5.0V
Continuous Forward Current 50mA
Peak Forward Current (1us) 1A
Power Dissipation. 100mW
Derate Linearly from $25^\circ C$ $1.3mW/^\circ C$

Detector (Output)

Output Breakdown Voltage $\pm 60V$
Continous Load Current $\pm 400mA$
Power Dissipation 500mW

General Characteristics

Isolation Test Voltage. 1500VAC RMS
Isolation Resistance
 $V_{10} = 500V, T_A = 25^\circ C$ $\geq 10^{10}\Omega$
Total Power Dissipation 550mW

Derate Linearly form $25^\circ C$ $2.5mW/^\circ C$
Storage Temperature Range -40 to $+150^\circ C$
Operating Temperature Range. -40 to $+85^\circ C$
Junction Temperature $100^\circ C$
Soldering Temperature, 2mm from case, 10 sec. $260^\circ C$

PRODUCT SPECIFICATION

DATE: 11/18/2003

COSMO ELECTRONICS CORPORATION	SOLID STATE RELAY-MOSFET OUTPUT KAQW212S	NO. 62M20006	REV. 1
		SHEET 2 OF 7	

Characteristics

($T_A = 25^\circ C$)

Description	Symbol	Min.	Typ.	Max.	Unit	Test Condition
Emitter (Input)						
Forward Voltage	V_F		1.2	1.5	V	$I_F = 10mA$
Operation Input Current	I_{FON}			5	mA	$V_L = \pm 20V, I_L = 100mA, t = 10ms$
Recovery Input Current	I_{FOFF}	0.2			mA	$V_L = \pm 20V, I_L < 5\mu A$
Deterctor (Output)						
Output Breakdown Voltage	V_B	60			V	$I_B = 50\mu A$
Output Off-State Leakage	I_{TOFF}		0.2	1	uA	$V_T = 60V, I_F = 0mA$
I/O Capacitance	C_{ISO}		6		pF	$I_F = 0, f = 1MHz$
ON Resistance	R_{ON}		0.83	2.50	Ω	$I_L = 100mA, I_F = 10mA$
Turn-on Time	T_{ON}		0.2	1.5	ms	$I_F = 10mA, V_L = \pm 20V$
Turn-off Time	T_{OFF}		0.3	1.5	ms	$t = 10ms, I_L = \pm 100mA$

Schematic and Wiring Diagrams

Type	Schematic	Output configuration	Load	Connection	Wiring diagram
KAQW212S		2a	AC/DC	-	<p>(1) Two independent 1 Form A use</p> <p>(2) 2 Form A use</p>


PRODUCT SPECIFICATION

DATE: 11/18/2003


COSMO ELECTRONICS CORPORATION	SOLID STATE RELAY-MOSFET OUTPUT KAQW212S	NO. 62M20006	REV.
		SHEET 3 OF 7	1

DATA CURVE


Load current vs. ambient temperature
Allowable ambient temperature:
-40°C to +85°C




On resistance vs. ambient temperature
Across terminals 5, 7 and 6, 8 pin
LED current: 5mA
Continuous load current: 130 mA(DC)



Turn on time vs. ambient temperature
Load voltage 60 V(DC)
LED current : 5mA
Continuous load current: 130mA(DC)



Turn off time vs. ambient temperature
LED current: 5mA; Load voltage: 60V(DC)
Continuous load current: 130mA(DC)




PRODUCT SPECIFICATION

DATE: 11/18/2003

COSMO ELECTRONICS CORPORATION	SOLID STATE RELAY-MOSFET OUTPUT KAQW212S	NO. 62M20006	REV. 1
		SHEET 4 OF 7	


LED operate vs. ambient temperature
Load voltage: 60V(DC)

Continuous load current: 130mA(DC)




LED turn off current vs. ambient temperature
Load voltage: 60V(DC)

Continuous load current: 130mA(DC)



LED dropout voltage vs. ambient temperature


LED current: 5 to 50mA



Voltage vs. current characteristics of output at MOS FET portion

Measured portion: across terminals 5, 6, 8 pin

Ambient temperature: 25 ° C




PRODUCT SPECIFICATION


DATE:11/18/2003

COSMO ELECTRONICS CORPORATION	SOLID STATE RELAY-MOSFET OUTPUT KAQW212S	NO. 62M20006	REV.
		SHEET 5 OF 7	1


LED forward current vs. turn on time
Across terminals 5, 7 and 6, 8 pin; Load voltage: 60V(DC); Continuous load current: 130mA(DC); Ambient temperature: 25° C




Off state leakage current
Across terminals 5, 7 and 6, 8 pin
Ambient temperature: 25° C



LED forward current vs. turn off time
Across terminals 5, 7 and 6, 8 pin; Load voltage: 60V(DC); Continuous load current: 130 mA(DC); Ambient temperature: 25° C



Applied voltage vs. output capacitance
Across terminals 5, 7 and 6, 8 pin
Frequency: 1MHz; Ambient temperature: 25° C



PRODUCT SPECIFICATION


DATE: 11/18/2003

COSMO ELECTRONICS CORPORATION	SOLID STATE RELAY-MOSFET OUTPUT KAQW212S	NO. 62M20006	REV.
		SHEET 6 OF 7	1

USING METHODS


Examples of resistance value to control LED forward current I_F

($I_F = 5\text{mA}$)



E	R
3.3V	Approx. 330 ohm
5V	Approx. 640 ohm
12V	Approx. 1.9K ohm
15V	Approx. 2.5K ohm
24V	Approx. 4.1K ohm

- (1) LED forward current must be more than 5mA, at E min.
- (2) LED forward current must be less than 50mA, at E max.





PRODUCT SPECIFICATION

DATE: 11/18/2003

COSMO ELECTRONICS CORPORATION	SOLID STATE RELAY-MOSFET OUTPUT KAQW212S	NO. 62M20006	REV.
		SHEET 7 OF 7	1

USING METHODS

Regulate the spike voltage generated on the inductive load as follows



R-C Snubber