

6448 M

DC axial compact fan



ebm-papst St. Georgen GmbH & Co. KG

Hermann-Papst-Straße 1

74673 St. Georgen

Phone: +49 7724 81-0

Fax: +49 7724 81-1309

www.ebmpapst.com

info2@de.ebmpapst.com

Nominal data

| Type | 6448 M | |
|--------------------------|----------------------|------|
| Nominal voltage | [VDC] | 48 |
| Speed | [min ⁻¹] | 2850 |
| Power input | [W] | 11.5 |
| Min. ambient temperature | [°C] | -20 |
| Max. ambient temperature | [°C] | 72 |
| Air flow | [m ³ /h] | 350 |
| Sound power level | [B] | 6.0 |
| Sound pressure level | [dB(A)] | 52 |

ml = max. load · me = max. efficiency · rfa = running at free air · cs = customer specs · cu = customer unit
Subject to alterations

Technical features

| | |
|--|---|
| Dimensions | 172 x 150 x 51 mm |
| General description | Diagonal fan with low noise when there is a high pressure saddle curve. Very rigid compression curve for high air flow at high counterpressure. Electronic commutation completely integrated. |
| Connection line | Flat plugs 3.0 x 0.5 mm. |
| Locked-rotor protection | Electronic blocking protection, with electronic motor current limit in the startup phase and when the rotor is blocked. |
| Direction of protection | Left, looking at rotor |
| Direction of air flow | Air exhaust over bars |
| Bearing | Ball bearings |
| Lifetime L10 at 40 °C | 80000 h |
| Lifetime L10 at maximum temperature | 37500 h |
| Mass | 0.760 kg |
| Material of impeller | Fiberglass-reinforced PA plastic |
| Motor protection | Protected against reverse polarity and locking. |
| Approval | VDE, CSA, UL, CE |

Product drawing



Charts: Air flow

