

[illegible][illegible]

Item	Symbol	Test Condition	Standard Value			
			Min.	Typ.	Max.	Unit
Power Supply Voltage	$V_{DD}-V_{SS}$	25°C	4.5	5.0	5.5	V
LCD Operation Voltage	V_{OP}		-	9.5	-	V
LCM Current Consumption	I_{DD}		-	9.0	15.0	mA
Backlight Forward Voltage	V_F		-	4.0	-	V

4.0 ABSOLUTE MAXIMUM RATINGS

Item	Symbol	Test Condition	Standard Value		
			Min.	Max.	Unit
Supply Voltage (Logic)	$V_{DD}-V_{SS}$	25°C	-0.3	7.0	V
Supply Voltage (LCD)	$V_{DD}-V_O$		-0.3	17.5	V
Input Voltage	V_{IN}		-0.3	$V_{DD}+0.3$	V
Operating Temp.	T_{OPR}	-	0	50	°C
Storage Temp.	T_{STG}	-	-20	70	°C

5.0 PIN ASSIGNMENT

PIN No.	Symbol	Description
1~8	DB0~DB7	Data bus
9	E	Enable signal
10	R/W	Read/Write selection H: Read L: Write
11	D/I	Register selection H: Display data, L: Instruction
12	nc	No connection
13	V_{DD}	Power supply
14	GND	Power supply(GND)
15	LEDK	LED Back-light
16	LEDA	LED Back-light
17	CS1	Chip select signal for IC1
18	CS2	Chip select signal for IC2

Remark

1. LCD option: STN, FSTN .
2. Standard module.
3. Backlight option: LED backlight feature, other specs not available on catalog is under request.