

MA SERIES
P3AU-XXXXE 1KV ISOLATED 0,5W UNREGULATED SINGLE OUTPUT SIP4
Available Inputs:
5, 12 and 24 VDC
Available Outputs:
3.3, 5, 7.2, 12, 15 and 18 VDC

Other specifications please enquire.

Electrical Specifications

(Typical at + 25° C, nominal input voltage, rated output current unless otherwise specified)

Input Specifications

 Voltage range +/- 10 %
 Filter Capacitors

Isolation Specifications

 Rated voltage 1000 VDC
 Leakage current 1 mA
 Resistance 10^9 Ohm
 Capacitance 60 pF typ.

Output Specifications

 Voltage accuracy +/- 5 %, max.
 Ripple and noise (at 20 MHz BW) 100 mV p-p, max.
 Short circuit protection Momentary
 Line voltage regulation +/- 1,2 % / 1,0 % of Vin
 Load voltage regulation +/- 8 %, load = 20 ~ 100 %
 Temperature coefficient +/- 0,02 % / °C

General Specifications

 Efficiency 75 % to 85 %
 Switching frequency 80 KHz, typ.

Environmental Specifications

 Operating temperature (ambient) - 40° C to + 85° C
 Storage temperature - 55 °C to + 125 °C
 Derating See graph
 Humidity Up to 90 %, non condensing
 Cooling Free air convection


Physical Characteristics

 Dimensions SIP 11.68 x 6.00 x 10.16 mm
 0.46 x 0,24 x 0,40 inches
 Weight 1,8 g
 Case material Non conductive black plastic


Examples of Partnumbers

PART NO.	INPUT VOLTAGE (VDC)	INPUT CURRENT NO LOAD	INPUT CURRENT FULL LOAD	OUTPUT VOLTAGE (VDC)	OUTPUT CURRENT (max. mA)	EFFICIENCY FULL LOAD (% TYP.)
P3AU-053R3E	5	16	133	3,3	150	74
P3AU-0505E	5	16	135	5	100	74
P3AU-057R2E	5	16	134	7,2	70	75
P3AU-0512E	5	16	133	12	42	76
P3AU-1205E	12	14	56	05	100	74
P3AU-1212E	12	14	55	12	42	76
P3AU-2405E	24	8	29	05	100	72

Dimensions



Derating Graph and Pinning



Specification can be changed without notice.

Copyright 2001 PEAK electronics GmbH