

## Dual N-Channel 40-V (D-S) MOSFET

### PRODUCT SUMMARY

<b>V<sub>DS</sub> (V)</b>	<b>r<sub>DS(on)</sub> (Ω)</b>	<b>I<sub>D</sub> (A)<sup>a</sup></b>	<b>Q<sub>g</sub> (Typ)</b>
40	0.027 at V <sub>GS</sub> = 10 V	6.0	9.6
	0.032 at V <sub>GS</sub> = 4.5 V	4.8	


### FEATURES

- TrenchFET® Power MOSFET
- 100 % R<sub>g</sub> and UIS Tested




### APPLICATIONS

- CCFL Inverter



Ordering Information: Si4910DY-T1-E3 (Lead (Pb)-free)



N-Channel MOSFET

N-Channel MOSFET

### ABSOLUTE MAXIMUM RATINGS (T<sub>A</sub> = 25 °C UNLESS OTHERWISE NOTED)

Parameter	Symbol	Limit	Unit
Drain-Source Voltage	V <sub>DS</sub>	40	V
Gate-Source Voltage	V <sub>GS</sub>	±16	
Continuous Drain Current (T <sub>J</sub> = 150 °C)	I <sub>D</sub>	7.6	
		6.0	
		6.0 <sup>b, c</sup>	
		4.8 <sup>b, c</sup>	
Pulsed Drain Current (10 µs Pulse Width)	I <sub>DM</sub>	20	A
Source-Drain Current Diode Current	I <sub>S</sub>	2.6	
		1.6 <sup>b, c</sup>	
Pulsed Source-Drain Current	I <sub>SM</sub>	20	
Single Pulse Avalanche Current	I <sub>AS</sub>	10	mJ
Single Pulse Avalanche Energy	E <sub>AS</sub>	5	
Maximum Power Dissipation	P <sub>D</sub>	3.1	W
		2	
		2 <sup>b, c</sup>	
		1.28 <sup>b, c</sup>	
Operating Junction and Storage Temperature Range	T <sub>J</sub> , T <sub>stg</sub>	-55 to 150	°C

### THERMAL RESISTANCE RATINGS

Parameter	Symbol	Typ	Max	Unit
Maximum Junction-to-Ambient <sup>b, d</sup>	R <sub>thJA</sub>	49	62.5	°C/W
Maximum Junction-to-Foot (Drain)	R <sub>thJF</sub>	30	40	

Notes

- a. Based on T<sub>C</sub> = 25 °C.
- b. Surface Mounted on 1" x 1" FR4 Board.
- c. t = 10 sec.
- d. Maximum under steady state conditions is 120 °C/W.







**SPECIFICATIONS ( $T_J = 25^\circ\text{C}$  UNLESS OTHERWISE NOTED)**






Parameter	Symbol	Test Condition	Min	Typ <sup>a</sup>	Max	Unit
<b>Static</b>						
Drain-Source Breakdown Voltage	$V_{DS}$	$V_{GS} = 0 \text{ V}, I_D = 250 \mu\text{A}$	40			V
$V_{DS}$ Temperature Coefficient	$\Delta V_{DS}/T_J$	$I_D = 250 \mu\text{A}$		37		
		$I_D = 250 \mu\text{A}$		-5		
Gate Threshold Voltage	$V_{GS(\text{th})}$	$V_{DS} = V_{GS}, I_D = 250 \mu\text{A}$	0.6		2.0	
Gate-Body Leakage	$I_{GSS}$	$V_{DS} = 0 \text{ V}, V_{GS} = \pm 16 \text{ V}$		100		nA
Zero Gate Voltage Drain Current	$I_{DSS}$	$V_{DS} = 40 \text{ V}, V_{GS} = 0 \text{ V}$		1		$\mu\text{A}$
		$V_{DS} = 40 \text{ V}, V_{GS} = 0 \text{ V}, T_J = 55^\circ\text{C}$		10		
On-State Drain Current <sup>b</sup>	$I_{D(\text{on})}$	$V_{DS} = 5 \text{ V}, V_{GS} = 10 \text{ V}$	20			A
Drain-Source On-State Resistance <sup>b</sup>	$r_{DS(\text{on})}$	$V_{GS} = 10 \text{ V}, I_D = 6 \text{ A}$		0.022	0.027	$\Omega$
		$V_{GS} = 4.5 \text{ V}, I_D = 4.8 \text{ A}$		0.026	0.032	
Forward Transconductance <sup>b</sup>	$g_{fs}$	$V_{DS} = 15 \text{ V}, I_D = 6 \text{ A}$		20		S
<b>Dynamic<sup>a</sup></b>						
Input Capacitance	$C_{iss}$	N-Channel $V_{DS} = 20 \text{ V}, V_{GS} = 0 \text{ V}, f = 1 \text{ MHz}$		855		pF
Output Capacitance	$C_{oss}$			105		
Reverse Transfer Capacitance	$C_{rss}$			65		
Total Gate Charge	$Q_g$	$V_{DS} = 20 \text{ V}, V_{GS} = 10 \text{ V}, I_D = 5 \text{ A}$	21	32		nC
Gate-Source Charge	$Q_{gs}$	N-Channel $V_{DS} = 20 \text{ V}, V_{GS} = 4.5 \text{ V}, I_D = 5 \text{ A}$		9.6	14.5	
Gate-Drain Charge	$Q_{gd}$			2.3		
Gate Resistance	$R_g$			3.2		
Turn-On Delay Time	$t_{d(\text{on})}$	N-Channel $V_{DD} = 20 \text{ V}, R_L = 4 \Omega$ $I_D \approx 5 \text{ A}, V_{GEN} = 10 \text{ V}, R_g = 1 \Omega$		2.5	3.8	$\Omega$
Rise Time	$t_r$			6	12	
Turn-Off Delay Time	$t_{d(\text{off})}$			11	20	
Fall Time	$t_f$			24	36	
Turn-On Delay Time	$t_{d(\text{on})}$			6	12	
Rise Time	$t_r$	N-Channel $V_{DD} = 20 \text{ V}, R_L = 4 \Omega$ $I_D \approx 5 \text{ A}, V_{GEN} = 4.5 \text{ V}, R_g = 1 \Omega$		12	20	ns
Turn-Off Delay Time	$t_{d(\text{off})}$			60	90	
Fall Time	$t_f$			22	33	
Turn-On Delay Time	$t_{d(\text{on})}$			5	10	
Rise Time	$t_r$					
<b>Drain-Source Body Diode Characteristics</b>						
Continuous Source-Drain Diode Current	$I_S$	$T_C = 25^\circ\text{C}$			2.6	A
Pulse Diode Forward Current <sup>a</sup>	$I_{SM}$				20	
Body Diode Voltage	$V_{SD}$	$I_S = 1.5 \text{ A}$		0.73	1.2	V
Body Diode Reverse Recovery Time	$t_{rr}$	N-Channel $I_F = 5 \text{ A}, dI/dt = 100 \text{ A}/\mu\text{s}, T_J = 25^\circ\text{C}$		26	40	ns
Body Diode Reverse Recovery Charge	$Q_{rr}$			21	32	nC
Reverse Recovery Fall Time	$t_a$			13		ns
Reverse Recovery Rise Time	$t_b$			13		




## Notes

- a. Guaranteed by design, not subject to production testing.  
 b. Pulse test; pulse width  $\leq 300 \mu\text{s}$ , duty cycle  $\leq 2\%$ .

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.



**TYPICAL CHARACTERISTICS (25 °C UNLESS NOTED)**


**TYPICAL CHARACTERISTICS (25 °C UNLESS NOTED)**

**TYPICAL CHARACTERISTICS (25 °C UNLESS NOTED)**


\*The power dissipation  $P_b$  is based on  $T_{J(\max)} = 150$  °C, using junction-to-case thermal resistance, and is more useful in settling the upper dissipation limit for cases where additional heatsinking is used. It is used to determine the current rating, when this rating falls below the package limit.

## **TYPICAL CHARACTERISTICS (25 °C UNLESS NOTED)**



Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see <http://www.vishay.com/bpa?73699>.



## Legal Disclaimer Notice

Vishay

### Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.