

ILX207DW

Interface IC of data serial transfer with one supply voltage

Interface transceivers of serial data as per RS - 232 MAX207 standard with one supply voltage and transmitter bipolar output voltage formed by the embedded voltage multiplication oscillator on 4 external capacitances equal to 0,1mkF, corresponding to EIA/TIA-232E, V.28 standards, are purposed for application in up-to-date high-performance calculating systems, high-speed electronic devices with high reliability of information exchange between remote objects.


Functions:

- 5 transmitters and 3 receivers of serial data as per RS – 232 standards

Truth table

Inputs	Outputs
R_{IN}, T_{IN}	R_{OUT}, T_{OUT}
H	L
L	H

Note -
H – high voltage level;
L – low voltage level



Packaged IC marking

ILX207DW SOIC

T_A = from -40 to 85 °C




Figure 1 – Symbols of pins in package

ILX207DW




Figure 2 - Block-diagram

Pin description

Pin number	Pin name	Symbol
01	Transmitter data output (levels RS – 232)	T3 _{OUT}
02	Transmitter data output (levels RS – 232)	T1 _{OUT}
03	Transmitter data output (levels RS – 232)	T2 _{OUT}
04	Receiver data input (levels RS – 232)	R1 _{IN}
05	Receiver data output (levels TTL/CMOS)	R1 _{OUT}
06	Transmitter data input (levels TTL/CMOS)	T2 _{IN}
07	Transmitter data input (levels TTL/CMOS)	T1 _{IN}
08	Common output	GND
09	Supply output from voltage source	V _{CC}
10	Output of external capacitance of positive voltage multiplication block	C1+
11	Output of multiplication block positive voltage	V+
12	Output of external capacitance of positive voltage multiplication block	C1-
13	Output of external capacitance of negative voltage multiplication block	C2+
14	Output of external capacitance of negative voltage multiplication block	C2-
15	Output of multiplication block negative voltage	V-
16	Receiver data input (levels RS – 232)	R3 _{IN}
17	Receiver data output (levels TTL/CMOS)	R3 _{OUT}
18	Transmitter data input (levels TTL/CMOS)	T3 _{IN}
19	Transmitter data input (levels TTL/CMOS)	T4 _{IN}
20	Transmitter data output (levels RS – 232)	T5 _{OUT}
21	Transmitter data input (levels TTL/CMOS)	T5 _{IN}
22	Receiver data output (levels TTL/CMOS)	R2 _{OUT}
23	Receiver data input (levels RS – 232)	R2 _{IN}
24	Transmitter data output (levels RS – 232)	T4 _{OUT}

ILX207DW

Absolute maximum ratings

Symbol	Parameter	Rate		Unit
		min	max	
V _{CC}	Supply voltage	-0.3	6.0	V
V-	Transmitter low output voltage	0.3	-14	
V+	Transmitter high output voltage	V _{CC} - 0.3 V	14	
VTIN	Transmitter input voltage	-0.3	V+ + 0.3 V	
VRIN	Receiver input voltage	-30	30	
PPK	Dissipated power (for copper frame)	-	941	mW
ISC	Transmitter short-circuit output current		continuously	mA
T _a	Ambient temperature	-60	150	°C

Maximum ratings

Symbol	Parameter	Rate		Unit
		min	max	
V _{CC}	Supply voltage	4.5	5.5	V
V-	Transmitter low output voltage	-5.0	-	
V+	Transmitter high output voltage	5.0		
VTIN	Transmitter input voltage	0	V _{CC}	
VRIN	Receiver input voltage	-30	30	
ISC	Transmitter short-circuit output current	-	±60	mA
T _a	Ambient temperature	-40	85	°C



ILX207DW

Static parameters

Symbol	Parameter	Test conditions	Rate				Unit	
			25°C		от -40 до 85 °C			
			min	max	min	max		
I _{CC}	Consumption current static	V _{CC} = 5.5 V V _{IL} = 0 V	-	20	-	28*	mA	

Receiver electrical parameters

V _H	Hysteresis voltage	V _{CC} = 5.0 V	0.2	0.9	0.2	1.0	V
V _{ON}	On voltage	V _{ON} ≤ 0.1 V I _{OL} ≤ 20 mKA	-	2.4	-	2.3	
V _{OFF}	Off voltage	V _O ≥ V _{CC} - 0.1 V I _{OH} ≤ -20 mKA	0.8	-	0.9	-	
V _{OL}	Low output voltage	I _{OL} = 1.6 mA V _{CC} = 4.5 V V _{IH} = 2.4 V	-	0.3	-	0.4	
V _{OH}	High output voltage	I _{OH} = -1.0 mA V _{CC} = 4.5 V V _{IL} = 0.8 V	3.6	-	3.5	-	
R _I	Input resistance	V _{CC} = 5.0 V	3.0	7.0	-		kOhm

Transmitter electrical parameters

V _{OL}	Low output voltage	V _{CC} = 4.5 V V _{IH} = 2.0 V R _L = 3.0 kOhm	-	-5.2	-	-5.0	V
V _{OH}	High output voltage	V _{CC} = 4.5 V V _{IL} = 0.8 V R _L = 3.0 kOhm	5.2	-	5.0	-	
I _{IL}	Low input current	V _{CC} = 5.5 V V _{IL} = 0 V	-	170	-	200	mkA
I _{SC}	Short-circuit output current	V _{CC} = 5.5 V V _O = 0 V V _{IL} = 0 V		-50		-60	mA
		V _{CC} = 5.5 V V _O = 0 V V _{IH} = V _{CC}		50		60	
R _O	Output resistance	V _{CC} =V+=V-= 0 V V _O = ±2 V	350	-	300	-	Ohm
SR	Speed of output front change	V _{CC} = 5.0 V, C _L = 50-1000 pF R _L = 3-7 kOhm	3.0	30	-		V/mksec
		V _{CC} = 4.5 V, R _L = 3 kOhm, C _L = 1000 pF, t _w = 7 mksec	140	-	120		
ST	Information transmission speed						Kbit/sec

Dynamic parameters (t_{LH} = t_{HL} ≤ 10 nsec)

Symbol	Parameter	Test conditions	Rate				Unit	
			25°C		from -40 to 85°C			
			min	max	min	max		



ILX207DW

t_{PHLR} (t_{PLHR})	Signal propagation delay time when switching on (off)	$V_{CC} = 4.5 \text{ V}$ $C_L = 150 \text{ pF}$ $V_{IL} = 0 \text{ V}$ $V_{IH} = 3.0 \text{ V}$	-	9.7	-	10.0	mksec
t_{PHLT} (t_{PLHT})	Signal propagation delay time when switching on (off)	$V_{CC} = 4.5 \text{ V}$ $C_L = 2500 \text{ pF}$ $V_{IL} = 0 \text{ V}$ $V_{IH} = 3.0 \text{ V}$ $R_L = 3 \text{ kOhm}$	5.0*		6.0*		

* Parameter ratings will be specified during experimental design

Timing diagrams when measuring IC dynamic parameters




Figure 3- Timing diagram when measuring propagation delay time when switching on t_{PHLR} , propagation delay time when switching off t_{PLHR}




Figure 4 – Timing diagram when measuring propagation delay time when switching on t_{PHLT} , propagation delay time when switching off t_{PLHT}




Figure 5 – Timing diagram of signals when measuring speed of output voltage SR change





Figure 6 – Timing diagram of signals when measuring speed of information ST transmission

Package overall dimensions

4322.24-A



Note:

1. Overall dimensions A and B are specified without taking fin and metal protuberances into consideration.
2. Presence of fin and metal protuberances for A – up to 0.15 mm (0.006) for side; for B – up to 0.25 mm (0.010) for side.

ILX207DW

Sign	Dimensions, mm	
	MIN	MAX
A	15.20	15.60
B	7.40	7.60
C	2.35	2.65
D	0.33	0.51
F	0.40	1.27
G	1.27	
H	9.53	
J	0°	8°
K	0.10	0.30
M	0.23	0.32
P	10.0	10.65
R	0.25	0.75

