


## Silicon NPN Power Transistors

... designed for medium-speed switching and amplifier applications. These devices feature:

- Total Switching Time at 3 A typically 1.15  $\mu$ s
- Gain Ranges Specified at 1 A and 3 A
- Low  $V_{CE(sat)}$ : typically 0.5 V at  $I_C = 5$  A and  $I_B = 0.5$  A
- Excellent Safe Operating Areas
- Complement to 2N3791-92

**NPN**  
**2N3715**  
**2N3716**


**10 AMPERE**  
**POWER TRANSISTORS**  
**SILICON NPN**  
**60-80 VOLTS**  
**150 WATTS**



**CASE 1-07**  
**TO-204AA**  
**(TO-3)**

### MAXIMUM RATINGS

Rating	Symbol	2N3715	2N3716	Unit
Collector-Emitter Voltage	$V_{CEO}$	60	80	Volts
Collector-Base Voltage	$V_{CB}$	80	100	Volts
Emitter-Base Voltage	$V_{EB}$	7.0	7.0	Volts
Collector Current	$I_C$	10	10	Amps
Base Current	$I_B$	4.0	4.0	Amps
Power Dissipation	$P_D$	150	150	Watts
Thermal Resistance	$\theta_{JC}$	1.17	1.17	$^{\circ}\text{C}/\text{W}$
Operating Junction and Storage Temperature Range	$T_J, T_{stg}$	-65 to +200		$^{\circ}\text{C}$



**Figure 1. Power-Temperature Derating Curve**

Safe Area Limits are indicated by Figures 12, 13. Both limits are applicable and must be observed.

REV 7



## 2N3715 2N3716




Figure 3. Collector Current versus Base Current




Figure 4. Base Current-Voltage Variations




Figure 5. Collector Current-Voltage Variations

NOTE 1. Dotted line indicates metered base current plus the  $I_{CBO}$  of the transistor at  $175^\circ\text{C}$ .

NOTE 2. Pulse test: pulse width  $\approx 200\ \mu\text{sec}$ , duty cycle  $\approx 1.5\%$ .




Figure 6. Collector-Emitter Saturation Voltage Variations




Figure 7. Base-Emitter Saturation Voltage Variations




Figure 8. Collector Current versus Base-Emitter Voltage




Figure 9. Collector Current versus Base-Emitter Resistance




Figure 10. Current Gain Variations




Figure 11. Current Gain — Bandwidth Product versus Collector Current

SAFE OPERATING AREAS




Figure 12. 2N3715





Figure 13. 2N3716

The Safe Operating Area Curves indicate  $I_C - V_{CE}$  limits below which the device will not go into secondary breakdown. Collector load lines for specific circuits must fall within the applicable Safe Area to avoid causing a collector-emitter

short. (Duty cycle of the excursions make no significant change in these safe areas.) To insure operation below the maximum  $T_J$ , the power-temperature derating curve must be observed for both steady state and pulse power conditions.

PACKAGE DIMENSIONS



- NOTES:  
 1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.  
 2. CONTROLLING DIMENSION: INCH.  
 3. ALL RULES AND NOTES ASSOCIATED WITH REFERENCED TO-204AA OUTLINE SHALL APPLY.

DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	1.550 REF		39.37 REF	
B	—	1.050	—	26.67
C	0.250	0.335	6.35	8.51
D	0.038	0.043	0.97	1.09
E	0.055	0.070	1.40	1.77
G	0.430 BSC		10.92 BSC	
H	0.215 BSC		5.46 BSC	
K	0.440	0.480	11.18	12.19
L	0.665 BSC		16.89 BSC	
N	—	0.830	—	21.08
Q	0.151	0.165	3.84	4.19
U	1.187 BSC		30.15 BSC	
V	0.131	0.188	3.33	4.77

- STYLE 1:  
 PIN 1: BASE  
 2: EMITTER  
 CASE: COLLECTOR

CASE 1-07  
 TO-204AA (TO-3)  
 ISSUE Z

Motorola reserves the right to make changes without further notice to any products herein. Motorola makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Motorola assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "Typical" parameters can and do vary in different applications. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. Motorola does not convey any license under its patent rights nor the rights of others. Motorola products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the Motorola product could create a situation where personal injury or death may occur. Should Buyer purchase or use Motorola products for any such unintended or unauthorized application, Buyer shall indemnify and hold Motorola and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that Motorola was negligent regarding the design or manufacture of the part. Motorola and are registered trademarks of Motorola, Inc. Motorola, Inc. is an Equal Opportunity/Affirmative Action Employer.

How to reach us:  
 USA/EUROPE: Motorola Literature Distribution;  
 P.O. Box 20912; Phoenix, Arizona 85036. 1-800-441-2447

JAPAN: Nippon Motorola Ltd.; Tatsumi-SPD-JLDC, Toshikatsu Otsuki,  
 6F Seibu-Butsuryu-Center, 3-14-2 Tatsumi Koto-Ku, Tokyo 135, Japan. 03-3521-8315

MFAX: RMFAX0@email.sps.mot.com - TOUCHTONE (602) 244-6609  
 INTERNET: http://Design-NET.com

HONG KONG: Motorola Semiconductors H.K. Ltd.; 8B Tai Ping Industrial Park,  
 51 Ting Kok Road, Tai Po, N.T., Hong Kong. 852-26629298

