

# GBPC40, 50/W SERIES

## 40, 50A GLASS PASSIVATED BRIDGE RECTIFIER

### Features

- Glass Passivated Die Construction
- Low Reverse Leakage Current
- Low Power Loss, High Efficiency
- Electrically Isolated Epoxy Case for Maximum Heat Dissipation
- Case to Terminal Isolation Voltage 2500V
- UL Recognized File # E157705


### Mechanical Data

- Case: Epoxy Case with Heat Sink Internally Mounted in the Bridge Encapsulation
- Terminals: Plated Leads Solderable per MIL-STD-202, Method 208
- Polarity: Symbols Marked on Case
- Mounting: Through Hole for #10 Screw
- Weight: GBPC 24 grams (approx.)  
GBPC-W 21 grams (approx.)
- Marking: Type Number

"W" Suffix Designates Wire Leads

No Suffix Designates Faston Terminals

\*All Models Available on Dim. B=7.9mm Max. Epoxy Case



	GBPC		GBPC-W	
Dim	Min	Max	Min	Max
A	28.40	28.70	28.40	28.70
*B	10.97	11.23	10.97	11.23
C	15.70	16.70	17.10	19.10
D	17.50	18.50	10.90	11.90
E	22.86	25.40	30.50	—
G	Hole for #10 screw, 5.08Ø Nominal			
H	6.35 Typical		0.97Ø	1.07Ø
All Dimension in mm				

### Maximum Ratings and Electrical Characteristics @T<sub>A</sub>=25°C unless otherwise specified

Single Phase, half wave, 60Hz, resistive or inductive load.

For capacitive load, derate current by 20%.

Characteristics	Symbol	-00/W	-01/W	-02/W	-04/W	-06/W	-08/W	-10/W	Unit
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	V <sub>RRM</sub> V <sub>RWM</sub> V <sub>R</sub>	50	100	200	400	600	800	1000	V
RMS Reverse Voltage	V <sub>R(RMS)</sub>	35	70	140	280	420	560	700	V
Average Rectifier Output Current @T <sub>C</sub> = 55°C	I <sub>O</sub>	40 50							A
Non-Repetitive Peak Forward Surge Current 8.3ms single half sine-wave Superimposed on rated load (JEDEC Method)	I <sub>FSM</sub>	400 400							A
Forward Voltage Drop (per element)	V <sub>FM</sub>	1.1							V
Peak Reverse Current At Rated DC Blocking Voltage	I <sub>RM</sub>	5.0 500							µA






---

**Maximum Ratings and Electrical Characteristics** @T<sub>A</sub>=25°C unless otherwise specified

---

Typical Junction Capacitance (per element) (Note 1)	C <sub>j</sub>	300	pF
Typical Thermal Resistance Junction to Case (per element) (Note 2)	R <sub>θJC</sub>	1.5	K/W
RMS Isolation Voltage from Case to Lead	V <sub>ISO</sub>	2500	V
Operating and Storage Temperature Range	T <sub>j</sub> , T <sub>STG</sub>	-65 to +150	°C

Note: 1. Measured at 1.0 MHz and applied reverse voltage of 4.0V D.C.  
2. Thermal resistance junction to case mounted on heatsink.



## ORDERING INFORMATION

Product No.	Package Type	Shipping Quantity
GBPCxx00	Square Bridge	50 Units/Box
GBPCxx00W	Square Bridge	50 Units/Box
GBPCxx01	Square Bridge	50 Units/Box
GBPCxx01W	Square Bridge	50 Units/Box
GBPCxx02	Square Bridge	50 Units/Box
GBPCxx02W	Square Bridge	50 Units/Box
GBPCxx04	Square Bridge	50 Units/Box
GBPCxx04W	Square Bridge	50 Units/Box
GBPCxx06	Square Bridge	50 Units/Box
GBPCxx06W	Square Bridge	50 Units/Box
GBPCxx08	Square Bridge	50 Units/Box
GBPCxx08W	Square Bridge	50 Units/Box
GBPCxx10	Square Bridge	50 Units/Box
GBPCxx10W	Square Bridge	50 Units/Box

Shipping quantity given is for minimum packing quantity only. For minimum order quantity, please consult the Sales Department.

Won-Top Electronics Co., Ltd (WTE) has checked all information carefully and believes it to be correct and accurate. However, WTE cannot assume any responsibility for inaccuracies. Furthermore, this information does not give the purchaser of semiconductor devices any license under patent rights to manufacturer. WTE reserves the right to change any or all information herein without further notice.

**WARNING:** DO NOT USE IN LIFE SUPPORT EQUIPMENT. WTE power semiconductor products are not authorized for use as critical components in life support devices or systems without the express written approval.

**Won-Top Electronics Co., Ltd.**

No. 44 Yu Kang North 3rd Road, Chine Chen Dist., Kaohsiung, Taiwan

**Phone:** 886-7-822-5408 or 886-7-822-5410

**Fax:** 886-7-822-5417

**Email:** sales@wontop.com

**Internet:** <http://www.wontop.com>

*We power your everyday.*