




## Surface Mount Glass Passivated Junction Fast Switching Rectifiers

Reverse Voltage 50 to 800V  
Forward Current 0.5A

DO-213AA

Patented\*



1st band denotes type and polarity  
2nd band denotes voltage type

\*Glass-plastic encapsulation is covered by  
Patent No. 3,996,602 and brazed-lead assembly to Patent No. 3,930,306



### Features

- Plastic package has Underwriters Laboratories Flammability Classification 94V-0
- For surface mount applications
- High temperature metallurgically bonded construction
- Cavity-free glass passivated junction
- Capable of meeting environmental standards of MIL-S-19500
- Fast switching for high efficiency
- High temperature soldering guaranteed: 450°C/5 seconds at terminals. Complete device submersible temperature of 260°C for 10 seconds in solder bath

### Mechanical Data

**Case:** JEDEC DO-213AA, molded plastic over glass body  
**Terminals:** Plated terminals, solderable per MIL-STD-750, Method 2026

**Polarity:** Two bands indicate cathode end – 1st band denotes device type and 2nd band denotes repetitive peak reverse voltage rating

**Mounting Position:** Any **Weight:** 0.0014 oz., 0.036 g  
**Packaging codes/options:**

33/9K per 13" Reel (8mm tape)  
48/2.5K per 7" Reel (8mm tape)

### Maximum Ratings & Thermal Characteristics Ratings at 25°C ambient temperature unless otherwise specified.

	Symbol	RGL34A	RGL34B	RGL34D	RGL34G	RGL34J	RGL34K	Unit
Fast switching device: 1st band is Red								
Polarity color bands (2nd Band)		Gray	Red	Orange	Yellow	Green	Blue	
Maximum repetitive peak reverse voltage	V <sub>RRM</sub>	50	100	200	400	600	800	V
Maximum RMS voltage	V <sub>RMS</sub>	35	70	140	280	420	560	V
Maximum DC blocking voltage	V <sub>DC</sub>	50	100	200	400	600	800	V
Max. average forward rectified current at T <sub>T</sub> = 55°C	I <sub>F(AV)</sub>	0.5						A
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	I <sub>FSM</sub>	10						A
Max. full load reverse current, full cycle average T <sub>A</sub> = 55°C	I <sub>R(AV)</sub>	30						μA
Maximum thermal resistance <sup>(1)</sup> <sup>(2)</sup>	R <sub>θJA</sub> R <sub>θJT</sub>	150 70						°C/W
Operating junction and storage temperature range	T <sub>J</sub> , T <sub>STG</sub>	-65 to +175						°C

### Electrical Characteristics Ratings at 25°C ambient temperature unless otherwise specified.

	Symbol	RGL34A	RGL34B	RGL34D	RGL34G	RGL34J	RGL34K	Unit
Maximum instantaneous forward voltage at 0.5A	V <sub>F</sub>	1.3						V
Maximum DC reverse current T <sub>A</sub> = 25°C T <sub>A</sub> = 125°C	I <sub>R</sub>	5.0 50						μA
Maximum reverse recovery time at I <sub>F</sub> = 0.5A, I <sub>R</sub> = 1.0A, I <sub>rr</sub> = 0.25A	t <sub>rr</sub>	150				250		ns
Typical junction capacitance at 4.0V, 1MHz	C <sub>J</sub>	4.0						pF

**Notes:** (1) Thermal resistance from junction to ambient, 0.2 x 0.2" (5.0 x 5.0mm) copper pads to each terminal  
(2) Thermal resistance from junction to terminal, 0.2 x 0.2" (5.0 x 5.0mm) copper pads to each terminal


# RGL34A thru RGL34K




Vishay Semiconductors  
formerly General Semiconductor

## Ratings and Characteristic Curves ( $T_A = 25^\circ\text{C}$ unless otherwise noted)


**Fig. 1 – Forward Current Derating Curve**




**Fig. 2 – Maximum Non-Repetitive Peak Forward Surge Current**



**Fig. 3 – Typical Instantaneous Forward Characteristics**



**Fig. 4 – Typical Reverse Characteristics**



**Fig. 5 – Typical Junction Capacitance**

