

# NTMS4872N

## Power MOSFET 30 V, 10.2 A, N-Channel, SO-8

### Features

- Low  $R_{DS(on)}$  to Minimize Conduction Losses
- Low Capacitance to Minimize Driver Losses
- Optimized Gate Charge to Minimize Switching Losses
- SOIC-8 Surface Mount Package Saves Board Space
- This is a Pb-Free Device

### Applications

- Disk Drives
- DC-DC Converters
- Printers

### MAXIMUM RATINGS ( $T_J = 25^\circ\text{C}$ unless otherwise stated)

| Parameter  | Symbol         | Value                    | Unit             |   |
|--|----------------|--------------------------|------------------|---|
| Drain-to-Source Voltage  | $V_{DS}$       | 30                       | V                |   |
| Gate-to-Source Voltage   | $V_{GS}$       | $\pm 20$                 | V                |   |
| Continuous Drain Current $R_{\theta JA}$ (Note 1)  | $I_D$          | $T_A = 25^\circ\text{C}$ | 8.0              | A |
|  |                | $T_A = 70^\circ\text{C}$ | 6.4              |   |
| Power Dissipation $R_{\theta JA}$ (Note 1)   | $P_D$          | $T_A = 25^\circ\text{C}$ | 1.49             | W |
|  |                | $T_A = 70^\circ\text{C}$ |                  |   |
| Continuous Drain Current $R_{\theta JA}$ (Note 2)  | $I_D$          | $T_A = 25^\circ\text{C}$ | 6.0              | A |
|  |                | $T_A = 70^\circ\text{C}$ | 4.8              |   |
| Power Dissipation $R_{\theta JA}$ (Note 2)   | $P_D$          | $T_A = 25^\circ\text{C}$ | 0.82             | W |
|  |                | $T_C = 25^\circ\text{C}$ |                  |   |
| Continuous Drain Current $R_{\theta JC}$ , $t \leq 10$ s (Note 1)  | $I_D$          | $T_C = 25^\circ\text{C}$ | 10.2             | A |
|  |                | $T_C = 70^\circ\text{C}$ | 8.2              |   |
| Power Dissipation $R_{\theta JC}$ , $t \leq 10$ s (Note 1)   | $P_D$          | $T_C = 25^\circ\text{C}$ | 2.4              | W |
|  |                | $T_C = 25^\circ\text{C}$ |                  |   |
| Pulsed Drain Current   | $I_{DM}$       | 56                       | A                |   |
| Operating Junction and Storage Temperature   | $T_J, T_{stg}$ | -55 to 150               | $^\circ\text{C}$ |   |
| Source Current (Body Diode)  | $I_S$          | 2.4                      | A                |   |
| Single Pulse Drain-to-Source Avalanche Energy ( $T_J = 25^\circ\text{C}$ , $V_{DD} = 30$ V, $V_{GS} = 10$ V, $I_L = 7.0$ A <sub>pk</sub> , $L = 1.0$ mH, $R_G = 25$ $\Omega$ ) | $E_{AS}$       | 24.5                     | mJ               |   |
| Lead Temperature for Soldering Purposes (1/8" from case for 10 s)  | $T_L$          | 260                      | $^\circ\text{C}$ |   |

### THERMAL RESISTANCE MAXIMUM RATINGS

| Parameter                                    | Symbol          | Value | Unit                      |
|--|-----------------|-------|---------------------------|
| Junction-to-Ambient – Steady State (Note 1)  | $R_{\theta JA}$ | 84    | $^\circ\text{C}/\text{W}$ |
| Junction-to-Ambient – $t \leq 10$ s (Note 1) | $R_{\theta JA}$ | 52    |                           |
| Junction-to-Foot (Drain)                     | $R_{\theta JF}$ | 22.5  |                           |
| Junction-to-Ambient – Steady State (Note 2)  | $R_{\theta JA}$ | 153   |                           |

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

1. Surfaced mounted on FR4 board using 1 sq-in pad, 2 oz Cu.
2. Surfaced mounted on FR4 board using the minimum recommended pad size.




ON Semiconductor®

<http://onsemi.com>


| $V_{(BR)DSS}$ | $R_{DS(ON)}$ MAX        | $I_D$ MAX |
|---------------|-------------------------|-----------|
| 30 V          | 13.5 m $\Omega$ @ 10 V  | 10.2 A    |
|               | 16.5 m $\Omega$ @ 4.5 V |           |

### N-Channel



SO-8  
CASE 751  
STYLE 12

### MARKING DIAGRAM/ PIN ASSIGNMENT



4872N = Device Code  
A = Assembly Location  
Y = Year  
WW = Work Week  
▪ = Pb-Free Package

(Note: Microdot may be in either location)

### ORDERING INFORMATION

| Device       | Package           | Shipping†        |
|--------------|-------------------|------------------|
| NTMS4872NR2G | SO-8<br>(Pb-Free) | 2500/Tape & Reel |

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specification Brochure, BRD8011/D.

# NTMS4872N

## ELECTRICAL CHARACTERISTICS ( $T_J = 25^\circ\text{C}$ unless otherwise specified)

| Parameter   | Symbol            | Test Condition                                  | Min                       | Typ | Max       | Unit          |
|---|-------------------|---|---------------------------|-----|-----------|---------------|
| <b>OFF CHARACTERISTICS</b>                                |                   |   |                           |     |           |               |
| Drain-to-Source Breakdown Voltage                         | $V_{(BR)DSS}$     | $V_{GS} = 0\text{ V}, I_D = 250\ \mu\text{A}$   | 30                        |     |           | V             |
| Drain-to-Source Breakdown Voltage Temperature Coefficient | $V_{(BR)DSS}/T_J$ |   |                           | 13  |           | mV/°C         |
| Zero Gate Voltage Drain Current                           | $I_{DSS}$         | $V_{GS} = 0\text{ V}, V_{DS} = 24\text{ V}$     | $T_J = 25^\circ\text{C}$  |     | 1.0       | $\mu\text{A}$ |
|   |                   |   | $T_J = 100^\circ\text{C}$ |     | 10        |               |
| Gate-to-Source Leakage Current                            | $I_{GSS}$         | $V_{DS} = 0\text{ V}, V_{GS} = \pm 20\text{ V}$ |                           |     | $\pm 100$ | nA            |

### ON CHARACTERISTICS (Note 3)

|  |                  |  |      |      |      |            |
|--|------------------|--|------|------|------|------------|
| Gate Threshold Voltage                     | $V_{GS(TH)}$     | $V_{GS} = V_{DS}, I_D = 250\ \mu\text{A}$    | 1.45 |      | 2.5  | V          |
| Negative Threshold Temperature Coefficient | $V_{GS(TH)}/T_J$ |  |      | 5.8  |      | mV/°C      |
| Drain-to-Source On Resistance              | $R_{DS(on)}$     | $V_{GS} = 10\text{ V}, I_D = 10.2\text{ A}$  |      | 9.4  | 13.5 | m $\Omega$ |
|  |                  | $V_{GS} = 4.5\text{ V}, I_D = 9.3\text{ A}$  |      | 13.5 | 16.5 |            |
| Forward Transconductance                   | $g_{FS}$         | $V_{DS} = 1.5\text{ V}, I_D = 10.2\text{ A}$ |      | 21   |      | S          |

### CHARGES, CAPACITANCES AND GATE RESISTANCE

|                              |              |  |  |      |      |    |
|------------------------------|--------------|--|--|------|------|----|
| Input Capacitance            | $C_{iss}$    | $V_{GS} = 0\text{ V}, f = 1.0\text{ MHz}, V_{DS} = 15\text{ V}$    |  | 1136 | 1700 | pF |
| Output Capacitance           | $C_{oss}$    |  |  | 240  | 370  |    |
| Reverse Transfer Capacitance | $C_{rss}$    |  |  | 130  | 200  |    |
| Total Gate Charge            | $Q_{G(TOT)}$ | $V_{GS} = 4.5\text{ V}, V_{DS} = 15\text{ V}, I_D = 10.2\text{ A}$ |  | 10   | 15   | nC |
| Threshold Gate Charge        | $Q_{G(TH)}$  |  |  | 1.3  |      |    |
| Gate-to-Source Charge        | $Q_{GS}$     |  |  | 3.4  | 5.0  |    |
| Gate-to-Drain Charge         | $Q_{GD}$     |  |  | 3.8  | 5.5  |    |
| Total Gate Charge            | $Q_{G(TOT)}$ | $V_{GS} = 10\text{ V}, V_{DS} = 15\text{ V}, I_D = 10.2\text{ A}$  |  | 20   | 30   | nC |

### SWITCHING CHARACTERISTICS (Note 4)

|                     |              |  |  |     |     |    |
|---------------------|--------------|--|--|-----|-----|----|
| Turn-On Delay Time  | $t_{d(on)}$  | $V_{GS} = 10\text{ V}, V_{DS} = 15\text{ V}, I_D = 10.2\text{ A}, R_G = 6.0\ \Omega$ |  | 10  | 15  | ns |
| Rise Time           | $t_r$        |  |  | 22  | 35  |    |
| Turn-Off Delay Time | $t_{d(off)}$ |  |  | 23  | 35  |    |
| Fall Time           | $t_f$        |  |  | 5.7 | 9.0 |    |

### DRAIN-SOURCE DIODE CHARACTERISTICS

|                         |          |  |                           |      |      |     |    |
|-------------------------|----------|--|---------------------------|------|------|-----|----|
| Forward Diode Voltage   | $V_{SD}$ | $V_{GS} = 0\text{ V}, I_S = 2.4\text{ A}$                                      | $T_J = 25^\circ\text{C}$  |      | 0.76 | 1.0 | V  |
|                         |          |  | $T_J = 125^\circ\text{C}$ |      | 0.6  |     |    |
| Reverse Recovery Time   | $t_{RR}$ | $V_{GS} = 0\text{ V}, dI_S/dt = 100\text{ A}/\mu\text{s}, I_S = 10.2\text{ A}$ |                           | 17.5 | 27   | ns  |    |
| Charge Time             | $t_a$    |  |                           | 8.5  | 13   |     |    |
| Discharge Time          | $t_b$    |  |                           | 9.0  | 14   |     |    |
| Reverse Recovery Charge | $Q_{RR}$ |  |                           | 6.5  | 10   |     | nC |

### PACKAGE PARASITIC VALUES

|                   |       |                          |  |      |     |          |
|-------------------|-------|--------------------------|--|------|-----|----------|
| Source Inductance | $L_S$ | $T_A = 25^\circ\text{C}$ |  | 0.66 |     | nH       |
| Drain Inductance  | $L_D$ |                          |  | 0.20 |     | nH       |
| Gate Inductance   | $L_G$ |                          |  | 1.5  |     | nH       |
| Gate Resistance   | $R_G$ |                          |  | 1.5  | 2.3 | $\Omega$ |

3. Pulse Test: pulse width = 300  $\mu\text{s}$ , duty cycle  $\leq 2\%$ .

4. Switching characteristics are independent of operating junction temperatures.

TYPICAL PERFORMANCE CURVES




Figure 1. On-Region Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance vs. Gate-to-Source Voltage




Figure 4. On-Resistance vs. Drain Current and Gate Voltage




Figure 5. On-Resistance Variation with Temperature




Figure 6. Drain-to-Source Leakage Current vs. Voltage

# NTMS4872N

## TYPICAL PERFORMANCE CURVES




Figure 7. Capacitance Variation




Figure 8. Gate-To-Source and Drain-To-Source Voltage vs. Total Charge




Figure 9. Resistive Switching Time Variation vs. Gate Resistance




Figure 10. Diode Forward Voltage vs. Current




Figure 11. Maximum Rated Forward Biased Safe Operating Area





Figure 12. Maximum Avalanche Energy vs. Starting Junction Temperature

# NTMS4872N

## PACKAGE DIMENSIONS

SOIC-8  
CASE 751-07  
ISSUE AJ




### NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. DIMENSION A AND B DO NOT INCLUDE MOLD PROTRUSION.
4. MAXIMUM MOLD PROTRUSION 0.15 (0.006) PER SIDE.
5. DIMENSION D DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.127 (0.005) TOTAL IN EXCESS OF THE D DIMENSION AT MAXIMUM MATERIAL CONDITION.
6. 751-01 THRU 751-06 ARE OBSOLETE. NEW STANDARD IS 751-07.

| DIM | MILLIMETERS |      | INCHES    |       |
|-----|-------------|------|-----------|-------|
|     | MIN         | MAX  | MIN       | MAX   |
| A   | 4.80        | 5.00 | 0.189     | 0.197 |
| B   | 3.80        | 4.00 | 0.150     | 0.157 |
| C   | 1.35        | 1.75 | 0.053     | 0.069 |
| D   | 0.33        | 0.51 | 0.013     | 0.020 |
| G   | 1.27 BSC    |      | 0.050 BSC |       |
| H   | 0.10        | 0.25 | 0.004     | 0.010 |
| J   | 0.19        | 0.25 | 0.007     | 0.010 |
| K   | 0.40        | 1.27 | 0.016     | 0.050 |
| M   | 0°          | 8°   | 0°        | 8°    |
| N   | 0.25        | 0.50 | 0.010     | 0.020 |
| S   | 5.80        | 6.20 | 0.228     | 0.244 |

### SOLDERING FOOTPRINT\*



### STYLE 12:

- PIN 1. SOURCE
- SOURCE
- SOURCE
- GATE
- DRAIN
- DRAIN
- DRAIN
- DRAIN

\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

ON Semiconductor and are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

### PUBLICATION ORDERING INFORMATION

#### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
Email: orderlit@onsemi.com

N. American Technical Support: 800-282-9855 Toll Free  
USA/Canada  
Europe, Middle East and Africa Technical Support:  
Phone: 421 33 790 2910  
Japan Customer Focus Center  
Phone: 81-3-5773-3850

ON Semiconductor Website: [www.onsemi.com](http://www.onsemi.com)

Order Literature: <http://www.onsemi.com/orderlit>

For additional information, please contact your local Sales Representative