

P-Channel 20-V (D-S) MOSFET

PRODUCT SUMMARY


V_{DS} (V)	$r_{DS(on)}$ (Ω)	I_D (A)	Q_g (Typ)
- 20	0.019 at $V_{GS} = - 4.5$ V	- 16 ^e	16.2 nC
	0.031 at $V_{GS} = - 2.5$ V	- 16 ^e	

FEATURES

- TrenchFET® Power MOSFET
- Low Thermal Resistance PowerPAK® Package with Small Size and Low 1.07 mm Profile
- PWM Optimized
- 100 % R_g and UIS Tested




PowerPAK 1212-8



Ordering Information: Si7601DN-T1-E3 (Lead (Pb)-free)

APPLICATIONS

- DC/DC Buck converter
- High-Side Application for Asynchronous Buck



P-Channel MOSFET

ABSOLUTE MAXIMUM RATINGS $T_A = 25$ °C, unless otherwise noted

Parameter	Symbol	Limit	Unit
Drain-Source Voltage	V_{DS}	- 20	V
Gate-Source Voltage	V_{GS}	± 12	
Continuous Drain Current ($T_J = 150$ °C)	I_D	- 16 ^e	A
		- 16 ^e	
		- 11.5 ^{a, b}	
		- 9.2 ^{a, b}	
Pulsed Drain Current	I_{DM}	- 40	
Continuous Source-Drain Diode Current	I_S	- 16 ^e	mA
		- 3.15 ^{a, b}	
Avalanche Current	I_{AS}	15	mJ
Single-Pulse Avalanche Energy	E_{AS}	11.25	
Maximum Power Dissipation	P_D	52	W
		33	
		3.8 ^{a, b}	
		2.4 ^{a, b}	
Operating Junction and Storage Temperature Range	T_J, T_{stg}	- 50 to 150	°C
Soldering Recommendations (Peak Temperature) ^{c, d}		260	

Notes:

- Surface Mounted on 1" x 1" FR4 board.
- t = 10 sec.
- See Solder Profile (<http://www.vishay.com/doc?73257>). The PowerPAK 1212-8 is a leadless package. The end of the lead terminal is exposed copper (not plated) as a result of the singulation process in manufacturing. A solder fillet at the exposed copper tip cannot be guaranteed and is not required to ensure adequate bottom side solder interconnection.
- Rework Conditions: manual soldering with a soldering iron is not recommended for leadless components.
- Package limited.

THERMAL RESISTANCE RATINGS

Parameter		Symbol	Typical	Maximum	Unit
Maximum Junction-to-Ambient ^{a, b}	$t \leq 10 \text{ sec}$	R_{thJA}	26	33	$^{\circ}\text{C/W}$
Maximum Junction-to-Case (Drain)	Steady State	R_{thJC}	1.9	2.4	

Notes:

- a. Surface Mounted on 1" x 1" FR4 board.
 b. Maximum under Steady State conditins is 81 $^{\circ}\text{C}/\text{W}$.







SPECIFICATIONS $T_J = 25 \text{ }^{\circ}\text{C}$, unless otherwise noted

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Static						
Drain-Source Breakdown Voltage	V_{DS}	$V_{GS} = 0 \text{ V}, I_D = - 250 \mu\text{A}$	- 20			V
V_{DS} Temperature Coefficient	$\Delta V_{DS}/T_J$	$I_D = - 250 \mu\text{A}$		- 16.8		$\text{mV}/^{\circ}\text{C}$
$V_{GS(\text{th})}$ Temperature Coefficient	$\Delta V_{GS(\text{th})}/T_J$			2.63		
Gate-Source Threshold Voltage	$V_{GS(\text{th})}$	$V_{DS} = V_{GS}, I_D = - 250 \mu\text{A}$	- 0.6		- 1.6	V
Gate-Source Leakage	I_{GSS}	$V_{DS} = 0 \text{ V}, V_{GS} = \pm 12 \text{ V}$			± 100	nA
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS} = - 20 \text{ V}, V_{GS} = 0 \text{ V}$			- 1	μA
		$V_{DS} = - 20 \text{ V}, V_{GS} = 0 \text{ V}, T_J = 55 \text{ }^{\circ}\text{C}$			- 10	
On-State Drain Current ^a	$I_{D(\text{on})}$	$V_{DS} \geq - 5 \text{ V}, V_{GS} = - 4.5 \text{ V}$	- 40			A
Drain-Source On-State Resistance ^a	$r_{DS(\text{on})}$	$V_{GS} = - 4.5 \text{ V}, I_D = - 11 \text{ A}$		0.016	0.0192	Ω
		$V_{GS} = - 2.5 \text{ V}, I_D = - 8.9 \text{ A}$		0.025	0.0313	
Forward Transconductance ^a	g_{fs}	$V_{DS} = - 10 \text{ V}, I_D = - 11 \text{ A}$		31.7		S
Dynamic^b						
Input Capacitance	C_{iss}	$V_{DS} = - 10 \text{ V}, V_{GS} = 0 \text{ V}, f = 1 \text{ MHz}$		1870		pF
Output Capacitance	C_{oss}			490		
Reverse Transfer Capacitance	C_{rss}			460		
Total Gate Charge	Q_g	$V_{DS} = - 10 \text{ V}, V_{GS} = - 5 \text{ V}, I_D = - 11 \text{ A}$		18	27	nC
Gate-Source Charge	Q_{gs}	$V_{DS} = - 10 \text{ V}, V_{GS} = - 4.5 \text{ V}, I_D = - 11 \text{ A}$		16.2	25	
Gate-Drain Charge	Q_{gd}			4.1		
Gate Resistance	R_g			4.8		
Turn-On Delay Time	$t_{d(\text{on})}$	$V_{DD} = - 10 \text{ V}, R_L = 1.09 \Omega$ $I_D \cong - 9.2 \text{ A}, V_{GEN} = - 4.5 \text{ V}, R_g = 1 \Omega$		6.1	9.2	Ω
Rise Time	t_r			18	27	ns
Turn-Off Delay Time	$t_{d(\text{off})}$			112	168	
Fall Time	t_f			53	80	
				80	120	
Drain-Source Body Diode Characteristics						
Continuous Source-Drain Diode Current	I_S	$T_C = 25 \text{ }^{\circ}\text{C}$			- 16	A
Pulse Diode Forward Current ^a	I_{SM}				- 40	
Body Diode Voltage	V_{SD}	$I_S = - 6 \text{ A}$		- 0.8	- 1.2	V
Body Diode Reverse Recovery Time	t_{rr}	$I_F = - 5 \text{ A}, di/dt = 100 \text{ A}/\mu\text{s}, T_J = 25 \text{ }^{\circ}\text{C}$		42	63	ns
Body Diode Reverse Recovery Charge	Q_{rr}			25.2	38	
Reverse Recovery Fall Time	t_a			14		ns
Reverse Recovery Rise Time	t_b			28		

Notes:






- a. Pulse test; pulse width $\leq 300 \mu\text{s}$, duty cycle $\leq 2 \%$.
 b. Guaranteed by design, not subject to production testing.



Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

**TYPICAL CHARACTERISTICS** 25 °C, unless otherwise noted**Output Characteristics****Transfer Characteristics****On-Resistance vs. Drain Current and Gate Voltage****Capacitance****Gate Charge****On-Resistance vs. Junction Temperature**

Si7601DN

Vishay Siliconix



**TYPICAL CHARACTERISTICS** 25 °C, unless otherwise noted

**TYPICAL CHARACTERISTICS** 25 °C, unless otherwise noted

*The power dissipation P_D is based on $T_{J(max)} = 150$ °C, using junction-to-case thermal resistance, and is more useful in settling the upper dissipation limit for cases where additional heatsinking is used. It is used to determine the current rating, when this rating falls below the package limit.

Si7601DN

Vishay Siliconix

**TYPICAL CHARACTERISTICS** 25 °C, unless otherwise noted

Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see <http://www.vishay.com/ppg?73778>.



Legal Disclaimer Notice

Vishay

Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.