


Glass Passivated Junction Fast Switching Rectifier

DO-204AL (DO-41)

 NOTE: Lead diameter is $\frac{0.026 \text{ (0.66)}}{0.023 \text{ (0.58)}}$ for suffix "E" part numbers

Dimensions in inches and (millimeters)

 *Glass-plastic encapsulation technique is covered by
 Patent No. 3,996,602, and brazed-lead assembly by Patent No. 3,930,306

 Reverse Voltage 200 to 1000V
 Forward Current 1.0A

Features

- Plastic package has Underwriters Laboratories Flammability Classification 94V-0
- High temperature metallurgically bonded construction
- For use in high frequency rectifier circuits
- Fast switching for high efficiency
- Cavity-free glass passivated junction
- Capable of meeting environmental standards of MIL-S-19500
- 1.0 Ampere operation at $T_A=55^\circ\text{C}$ with no thermal runaway
- High temperature soldering guaranteed:
 $350^\circ\text{C}/10$ seconds, 0.375" (9.5mm) lead length,
 5 lbs. (2.3kg) tension

Mechanical Data

Case: JEDEC DO-204AL, molded plastic over glass body

Terminals: Plated axial leads, solderable per
 MIL-STD-750, Method 2026

Polarity: Color band denotes cathode end

Mounting Position: Any

Weight: 0.012 oz., 0.3 g

Maximum Ratings & Thermal Characteristics

 Ratings at 25°C ambient temperature unless otherwise specified.

Parameter	Symbol	1N4942GP	1N4944GP	1N4946GP	1N4947GP	1N4948GP	Unit
* Maximum repetitive peak reverse voltage	V _{RRM}	200	400	600	800	1000	V
* Maximum RMS voltage	V _{RMS}	140	280	420	560	700	V
* Maximum DC blocking voltage	V _{DC}	200	400	600	800	1000	V
* Maximum average forward rectified current 0.375" (9.5mm) lead length at $T_A=55^\circ\text{C}$	I _{F(AV)}				1.0		A
* Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	I _{FSM}				25		A
Typical thermal resistance ⁽¹⁾	R _{θJA}			55			°C/W
* Operating junction and storage temperature range	T _J , T _{STG}			-65 to +175			°C

Electrical Characteristics

 Ratings at 25°C ambient temperature unless otherwise specified.

* Maximum instantaneous forward voltage at 1.0A	V _F	1.3			V
* Maximum DC reverse current at rated DC blocking voltage	T _A = 25°C T _A = 150°C	1.0 200			µA
* Maximum reverse recovery time at I _F =0.5A, I _R =1.0A, I _{rr} =0.25A	t _{rr}	150 250 500			ns
Typical junction capacitance at 4.0V, 1MHz	C _J	15			pF

Notes:

 (1) Thermal resistance from junction to ambient, and from junction to lead at 0.375" (9.5mm) lead length, P.C.B. mounted
 *JEDEC registered values


1N4942GP thru 1N4942GP




Vishay Semiconductors
formerly General Semiconductor

Ratings and Characteristic Curves (TA = 25°C unless otherwise noted)


**Fig. 1 — Forward Current
Derating Curves**



**Fig. 2 — Maximum Non-Repetitive
Peak Forward Surge Current**



**Fig. 3 — Typical Instantaneous
Forward Characteristics**



**Fig. 4 — Typical Reverse
Characteristics**





Fig. 5 — Typical Junction Capacitance



**Fig. 6 — Typical Transient
Thermal Impedance**

