

# Φ40 Body Standard / Hollow Shaft Type

## Diameter Φ 40mm Shaft type/Hollow type/Built-in type INCREMENTAL Rotary encoder

### ■ Features

- Easy installation at narrow space
- Small inertia moment
- Wide range of power source :  
5VDC, 12~24VDC ±5%
- Various output types

**⚠ Please read "Caution for your safety" in operation manual before using.**



### ■ Ordering information

E40	[H]	8	—	5000	—	3	—	2	—	24	—	
Series	Shaft type	Hollow type	Pulse/1Revolution	Output phase	Output	Power supply	Cable					
S:Shaft type	Outside	Inside		2:A, B	1:Totem pole output	5 :5VDC ±5%	No mark:Normal type					
H:Hollow type	(*)	6: φ6mm 8: φ8mm	See resolution	3:A, B, Z 4:A, $\overline{A}$ , B, $\overline{B}$ 6:A, $\overline{A}$ , B, $\overline{B}$ , Z, $\overline{Z}$	2:NPN open collector output 3:Voltage output L:Line driver output(*)	24:12~24VDC ±5%	(*) 2C:Cable outgoing connector type					
HB:Hollow built-in type	No mark: φ6mm 8: φ8mm	10: φ10mm 12: φ12mm										
※Standard : E40S6-[PULSE]-3-2-24 E40H8-[PULSE]-3-2-24 E40HB8-[PULSE]-3-2-24	12~24VDC	※Standard:A, B, Z The power of Line driver is only for 5VDC	※Cable length : 200mm									

### ■ Specifications

Item	Diameter Φ 40mm shaft type Incremental Rotary encoder																																																																																															
Resolution(P/R)	(★Note1) *1, *2, *5, 10, *12, 15, 20, 23, 25, 30, 35, 40, 45, 50, 60, 75, 100, 120, 150, 192, 200, 240, 250, 256, 300, 360, 400, 500, 512, 600, 800, 1000, 1024, 1200, 1500, 1800, 2000, 2048, 2500, 3000, 3600, 5000 (Not indicated type is available to customize)																																																																																															
Electrical specification	<table border="0"> <tr> <td>Phase difference of output</td> <td>Output between A and B phase : <math>\frac{T}{4} \pm \frac{T}{8}</math> (T=1cycle of A phase)</td> </tr> <tr> <td rowspan="3">Control output</td> <td>Totem pole output</td> <td>• Low ⚡ Load current : Max. 30mA, Residual voltage : Max. 0.4VDC • High ⚡ Load current : Max. 10mA, Output voltage : Min. (Power voltage - 1.5)VDC</td> </tr> <tr> <td>NPN open collector output</td> <td>Load current : Max. 30mA, Residual voltage : Max. 0.4VDC</td> </tr> <tr> <td>Voltage output</td> <td>Load current : Max. 10mA, Residual voltage : Max. 0.4VDC</td> </tr> <tr> <td rowspan="3">Response time (Rese/Fall)</td> <td>Line driver output</td> <td>Low ⚡ Load current : Max. 20mA, Residual : Max. 0.5V High ⚡ Load current : Max. -20mA, Output voltage : Min. 2.5V</td> </tr> <tr> <td>Totem pole output</td> <td>Max. 1μs</td> </tr> <tr> <td>NPN open collector output</td> <td>Max. 1μs</td> </tr> <tr> <td rowspan="3">Mechanical specification</td> <td>Voltage output</td> <td>Max. 1μs</td> </tr> <tr> <td>Line driver output</td> <td>Max. 0.5μs</td> </tr> <tr> <td>Max. Response frequency</td> <td>180kHz</td> </tr> <tr> <td>Current consumption</td><td colspan="3">Max. 60mA (disconnection of the load), Line driver output:Max. 50mA (disconnection of the load)</td></tr> <tr> <td>Insulation resistance</td><td colspan="3">Min. 100MΩ (at 500VDC)</td></tr> <tr> <td>Dielectric strength</td><td colspan="3">750VAC 50/60Hz for 1 minute(Between all terminals and case)</td></tr> <tr> <td>Connection</td><td colspan="3">Cable outgoing type, 200mm cable outgoing connector type</td></tr> <tr> <td>Starting torque</td><td colspan="3">Shaft Type : Max. 40gf · cm(0.004N · m), Hollow Type : Max. 50gf · cm(0.005N · m)</td></tr> <tr> <td>Moment of inertia</td><td colspan="3">Max. 40g · cm² (2 × 40⁻⁶ kg · m²)</td></tr> <tr> <td>Shaft loading</td><td colspan="3">Radial : Max. 2kgf, Thrust : Max. 1kgf</td></tr> <tr> <td>Deviation of shaft position</td><td colspan="3">Radial : Max. 0.1mm, Thrust : Max. 0.2mm</td></tr> <tr> <td>Max. allowable revolution</td><td colspan="3">(★Note2) 5000rpm</td></tr> <tr> <td>Vibration</td><td colspan="3">1.5mm amplitude at frequency of 10 ~ 55Hz in each of X, Y, Z directions for 2 hours</td></tr> <tr> <td>Shock</td><td colspan="3">Max. 50G</td></tr> <tr> <td>Ambient temperature</td><td colspan="3">-10 ~ 70°C (at non-freezing status), Storage:-25 ~ 85°C</td></tr> <tr> <td>Ambient humidity</td><td colspan="3">35~85%RH, Storage: 35~90%RH</td></tr> <tr> <td>Protection</td><td colspan="3">IP50(IEC specification)</td></tr> <tr> <td>Cable</td><td colspan="3">5P, φ 5mm, Length : 2m, Shield cable (Line driver output : 8P, φ 5mm)</td></tr> <tr> <td>Accessory</td><td colspan="3">φ 6mm coupling standard, φ 8mm coupling(Option) [Applied only for shaft type]</td></tr> <tr> <td>Weight</td><td colspan="3">Approx. 120g</td></tr> <tr> <td>Approval</td><td colspan="3">CE (Except Line driver output)</td></tr> </table>	Phase difference of output	Output between A and B phase : $\frac{T}{4} \pm \frac{T}{8}$ (T=1cycle of A phase)	Control output	Totem pole output	• Low ⚡ Load current : Max. 30mA, Residual voltage : Max. 0.4VDC • High ⚡ Load current : Max. 10mA, Output voltage : Min. (Power voltage - 1.5)VDC	NPN open collector output	Load current : Max. 30mA, Residual voltage : Max. 0.4VDC	Voltage output	Load current : Max. 10mA, Residual voltage : Max. 0.4VDC	Response time (Rese/Fall)	Line driver output	Low ⚡ Load current : Max. 20mA, Residual : Max. 0.5V High ⚡ Load current : Max. -20mA, Output voltage : Min. 2.5V	Totem pole output	Max. 1μs	NPN open collector output	Max. 1μs	Mechanical specification	Voltage output	Max. 1μs	Line driver output	Max. 0.5μs	Max. Response frequency	180kHz	Current consumption	Max. 60mA (disconnection of the load), Line driver output:Max. 50mA (disconnection of the load)			Insulation resistance	Min. 100MΩ (at 500VDC)			Dielectric strength	750VAC 50/60Hz for 1 minute(Between all terminals and case)			Connection	Cable outgoing type, 200mm cable outgoing connector type			Starting torque	Shaft Type : Max. 40gf · cm(0.004N · m), Hollow Type : Max. 50gf · cm(0.005N · m)			Moment of inertia	Max. 40g · cm² (2 × 40⁻⁶ kg · m²)			Shaft loading	Radial : Max. 2kgf, Thrust : Max. 1kgf			Deviation of shaft position	Radial : Max. 0.1mm, Thrust : Max. 0.2mm			Max. allowable revolution	(★Note2) 5000rpm			Vibration	1.5mm amplitude at frequency of 10 ~ 55Hz in each of X, Y, Z directions for 2 hours			Shock	Max. 50G			Ambient temperature	-10 ~ 70°C (at non-freezing status), Storage:-25 ~ 85°C			Ambient humidity	35~85%RH, Storage: 35~90%RH			Protection	IP50(IEC specification)			Cable	5P, φ 5mm, Length : 2m, Shield cable (Line driver output : 8P, φ 5mm)			Accessory	φ 6mm coupling standard, φ 8mm coupling(Option) [Applied only for shaft type]			Weight	Approx. 120g			Approval	CE (Except Line driver output)		
Phase difference of output	Output between A and B phase : $\frac{T}{4} \pm \frac{T}{8}$ (T=1cycle of A phase)																																																																																															
Control output	Totem pole output	• Low ⚡ Load current : Max. 30mA, Residual voltage : Max. 0.4VDC • High ⚡ Load current : Max. 10mA, Output voltage : Min. (Power voltage - 1.5)VDC																																																																																														
	NPN open collector output	Load current : Max. 30mA, Residual voltage : Max. 0.4VDC																																																																																														
	Voltage output	Load current : Max. 10mA, Residual voltage : Max. 0.4VDC																																																																																														
Response time (Rese/Fall)	Line driver output	Low ⚡ Load current : Max. 20mA, Residual : Max. 0.5V High ⚡ Load current : Max. -20mA, Output voltage : Min. 2.5V																																																																																														
	Totem pole output	Max. 1μs																																																																																														
	NPN open collector output	Max. 1μs																																																																																														
Mechanical specification	Voltage output	Max. 1μs																																																																																														
	Line driver output	Max. 0.5μs																																																																																														
	Max. Response frequency	180kHz																																																																																														
Current consumption	Max. 60mA (disconnection of the load), Line driver output:Max. 50mA (disconnection of the load)																																																																																															
Insulation resistance	Min. 100MΩ (at 500VDC)																																																																																															
Dielectric strength	750VAC 50/60Hz for 1 minute(Between all terminals and case)																																																																																															
Connection	Cable outgoing type, 200mm cable outgoing connector type																																																																																															
Starting torque	Shaft Type : Max. 40gf · cm(0.004N · m), Hollow Type : Max. 50gf · cm(0.005N · m)																																																																																															
Moment of inertia	Max. 40g · cm² (2 × 40⁻⁶ kg · m²)																																																																																															
Shaft loading	Radial : Max. 2kgf, Thrust : Max. 1kgf																																																																																															
Deviation of shaft position	Radial : Max. 0.1mm, Thrust : Max. 0.2mm																																																																																															
Max. allowable revolution	(★Note2) 5000rpm																																																																																															
Vibration	1.5mm amplitude at frequency of 10 ~ 55Hz in each of X, Y, Z directions for 2 hours																																																																																															
Shock	Max. 50G																																																																																															
Ambient temperature	-10 ~ 70°C (at non-freezing status), Storage:-25 ~ 85°C																																																																																															
Ambient humidity	35~85%RH, Storage: 35~90%RH																																																																																															
Protection	IP50(IEC specification)																																																																																															
Cable	5P, φ 5mm, Length : 2m, Shield cable (Line driver output : 8P, φ 5mm)																																																																																															
Accessory	φ 6mm coupling standard, φ 8mm coupling(Option) [Applied only for shaft type]																																																																																															
Weight	Approx. 120g																																																																																															
Approval	CE (Except Line driver output)																																																																																															

  |  |  |


(M) 5-Phase stepping motor & Driver & Controller			
(L) Rotary encoder			
(K) Pressure sensor			
(J) Photo electric sensor			
(I) Proximity sensor			
(H) Sensor controller			
(G) Display unit			
(E) Panel meter			
(F) Tacho/ Speed/ Pulse meter			
(D) Power controller			
(C) Temp. controller			
(B) Timer			
(A) Counter			

\*(★Note1) \* pulse is only for A, B phase(Line Driver output is A,  $\overline{A}$ , B,  $\overline{B}$  phase)

\*(★Note2) Max. allowable revolution ≥ Max. response revolution [Max. response revolution(rpm) =  $\frac{\text{Max. response frequency}}{\text{Resolution}} \times 60 \text{ sec}$ ]  
Please select the resolution to make lower max. revolution than max. allowable revolution.

# E40 Series

## Control output diagram




※ Totem pole output type can be used for NPN open collector output type(※1) or Voltage output type(※2).

※ All output circuits are the same A, B, Z phase(Line driver output is A,  $\bar{A}$ , B,  $\bar{B}$ , Z,  $\bar{Z}$ )


## Output waveform

●Totem pole output / NPN open collector output / Voltage output



※Inverse type of Z phase is optional.

●Line driver output




※CW : In a view of shaft

## Connections

### Normal type

●Totem pole output / NPN open collector output / Voltage output




- Black:OUT A
- White:OUT B
- Orange:OUT Z
- Brown:+V(5VDC, 12~24VDC ±5%)
- Blue:GND(0V)
- Shield:F.G

※Unused wires must be insulated.

※The body of encoder is connected to a shield.

●Line driver output



- Black:OUT A
- Red:OUT  $\bar{A}$
- White:OUT B
- Gray:OUT  $\bar{B}$
- Orange:OUT Z
- Yellow:OUT  $\bar{Z}$
- Brown:+V(5VDC ±5%)
- Blue:GND(0V)
- Shield:F.G

### Cable outgoing connector type



Pin No.	Cable color	Totem pole output NPN open collector output Voltage output	Line driver output
①	Black	OUT A	OUT A
②	Red	N.C	OUT $\bar{A}$
③	Brown	+V	+V
④	Blue	GND	GND
⑤	White	OUT B	OUT B
⑥	Gray	N.C	OUT $\bar{B}$
⑦	Orange	OUT Z	OUT Z
⑧	Yellow	N.C	OUT $\bar{Z}$
⑨	Shield	F.G	F.G
⑩	Purple	N.C	N.C

※N.C(Not Connected)




※F.G(Field Ground)

# Φ40 Body Standard / Hollow Shaft Type






## Dimensions

### Normal type


- Shaft type



- Hollow shaft / Hollow shaft built-in type




A	φ6	φ8	φ10	φ12
B	φ15		φ17	
Tolerance			+0.015	-0




### Cable outgoing connector type

- Connector cable(Accessory)




Connector cable model		Connector cable model	
Line driver output	EC8-2(Standard), EC8-5, EC8-10	EC	5 - 2
Etc.	EC5-2(Standard), EC5-5, EC5-10	Cable length(m)	The number of cables Connector cable of Encoder


\*A cable length is optional.



- Coupling(E40S)  
[φ6 Coupling]



[φ8 Coupling]



Unit:mm

(A) Counter

(B) Timer

(C) Temp. controller

(D) Power controller

(E) Panel meter

(F) Tacho/ Speed/ Pulse meter

(G) Display unit

(H) Sensor controller

(I) Proximity sensor

(J) Photo electric sensor

(K) Pressure sensor

(L) Rotary encoder

(M) 5-Phase stepping motor & Driver & Controller