


- Rugged Triple-Diffused Planar Construction
- 15 A Continuous Collector Current
- 1000 Volt Blocking Capability



Pin 2 is in electrical contact with the mounting base.

MDTRAAA

absolute maximum ratings at 25°C case temperature (unless otherwise noted)

RATING		SYMBOL	VALUE	UNIT
Collector-emitter voltage ($V_{BE} = 0$ V)	BUV48 BUV48A	V_{CES}	850 1000	V
Collector-emitter voltage ($R_{BE} = 10 \Omega$)	BUV48 BUV48A	V_{CER}	850 1000	V
Collector-emitter voltage ($I_B = 0$)	BUV48 BUV48A	V_{CEO}	400 450	V
Continuous collector current		I_C	15	A
Peak collector current (see Note 1)		I_{CM}	30	A
Continuous base current		I_B	4	A
Peak base current		I_{BM}	20	A
Non repetitive accidental peak surge current		I_{CSM}	55	A
Continuous device dissipation at (or below) 25°C case temperature		P_{tot}	125	W
Operating junction temperature range		T_j	-65 to +150	°C
Storage temperature range		T_{stg}	-65 to +150	°C

NOTE 1: This value applies for $t_p \leq 2$ ms, duty cycle $\leq 2\%$.

PRODUCT INFORMATION

BUV48, BUV48A NPN SILICON POWER TRANSISTORS

BOURNS®

electrical characteristics at 25°C case temperature (unless otherwise noted)

PARAMETER		TEST CONDITIONS			MIN	TYP	MAX	UNIT
$V_{CEO(sus)}$	Collector-emitter sustaining voltage	$I_C = 200 \text{ mA}$	$L = 25 \text{ mH}$	(see Note 2)	BUV48 BUV48A	400 450		V
I_{CES}	Collector-emitter cut-off current	$V_{CE} = 850 \text{ V}$	$V_{BE} = 0$		BUV48		0.2	mA
		$V_{CE} = 1000 \text{ V}$	$V_{BE} = 0$		BUV48A		0.2	
		$V_{CE} = 850 \text{ V}$	$V_{BE} = 0$	$T_C = 125^\circ\text{C}$	BUV48		2.0	
		$V_{CE} = 1000 \text{ V}$	$V_{BE} = 0$	$T_C = 125^\circ\text{C}$	BUV48A		2.0	
I_{CER}	Collector-emitter cut-off current	$V_{CE} = 850 \text{ V}$	$R_{BE} = 10 \Omega$		BUV48		0.5	mA
		$V_{CE} = 1000 \text{ V}$	$R_{BE} = 10 \Omega$		BUV48A		0.5	
		$V_{CE} = 850 \text{ V}$	$R_{BE} = 10 \Omega$	$T_C = 125^\circ\text{C}$	BUV48		4.0	
		$V_{CE} = 1000 \text{ V}$	$R_{BE} = 10 \Omega$	$T_C = 125^\circ\text{C}$	BUV48A		4.0	
I_{EBO}	Emitter cut-off current	$V_{EB} = 5 \text{ V}$	$I_C = 0$				1	mA
V_{EBO}	Emitter-base breakdown voltage	$I_E = 50 \text{ mA}$	$I_C = 0$		7		30	V
$V_{CE(sat)}$	Collector-emitter saturation voltage	$I_B = 2 \text{ A}$	$I_C = 10 \text{ A}$		BUV48		1.5	V
		$I_B = 3 \text{ A}$	$I_C = 15 \text{ A}$		BUV48		5.0	
		$I_B = 1.6 \text{ A}$	$I_C = 8 \text{ A}$	(see Notes 3 and 4)	BUV48A		1.5	
		$I_B = 2.4 \text{ A}$	$I_C = 12 \text{ A}$		BUV48A		5.0	
$V_{BE(sat)}$	Base-emitter saturation voltage	$I_B = 2 \text{ A}$	$I_C = 10 \text{ A}$		BUV48		1.6	V
		$I_B = 1.6 \text{ A}$	$I_C = 8 \text{ A}$	(see Notes 3 and 4)	BUV48A		1.6	
f_t	Current gain bandwidth product	$V_{CE} = 10 \text{ V}$	$I_C = 0.5 \text{ A}$	$f = 1 \text{ MHz}$			10	MHz
C_{ob}	Output capacitance	$V_{CB} = 20 \text{ V}$	$I_C = 0$	$f = 1 \text{ MHz}$			150	pF

NOTES: 2. Inductive loop switching measurement.

3. These parameters must be measured using pulse techniques, $t_p = 300 \mu\text{s}$, duty cycle $\leq 2\%$.

4. These parameters must be measured using voltage-sensing contacts, separate from the current carrying contacts.

thermal characteristics

PARAMETER		MIN	TYP	MAX	UNIT
$R_{\theta JC}$	Junction to case thermal resistance			1	°C/W

resistive-load-switching characteristics at 25°C case temperature

PARAMETER		TEST CONDITIONS [†]			MIN	TYP	MAX	UNIT
t_{on}	Turn on time	$I_C = 10 \text{ A}$	$V_{CC} = 150 \text{ V}$	BUV48			1.0	μs
t_s	Storage time	$I_{B(on)} = 2 \text{ A}$	$I_{B(off)} = -2 \text{ A}$	(see Figures 1 and 2)			3.0	μs
t_f	Fall time						0.8	μs
t_{on}	Turn on time	$I_C = 8 \text{ A}$	$V_{CC} = 150 \text{ V}$	BUV48A			1.0	μs
t_s	Storage time	$I_{B(on)} = 1.6 \text{ A}$	$I_{B(off)} = -1.6 \text{ A}$	(see Figures 1 and 2)			3.0	μs
t_f	Fall time						0.8	μs

[†] Voltage and current values shown are nominal; exact values vary slightly with transistor parameters.

inductive-load-switching characteristics at 100°C case temperature

PARAMETER		TEST CONDITIONS [†]			MIN	TYP	MAX	UNIT
t_{sv}	Voltage storage time	$I_C = 10 \text{ A}$	$I_{B(on)} = 2 \text{ A}$	BUV48			4.0	μs
t_{fi}	Current fall time	$V_{BE(off)} = -5 \text{ V}$	(see Figures 3 and 4)				0.4	μs
t_{sv}	Voltage storage time	$I_C = 8 \text{ A}$	$I_{B(on)} = 1.6 \text{ A}$	BUV48A			4.0	μs
t_{fi}	Current fall time	$V_{BE(off)} = -5 \text{ V}$	(see Figures 3 and 4)				0.4	μs

PRODUCT INFORMATION

PARAMETER MEASUREMENT INFORMATION




Figure 1. Resistive-Load Switching Test Circuit




Figure 2. Resistive-Load Switching Waveforms

PRODUCT INFORMATION

PARAMETER MEASUREMENT INFORMATION





Figure 3. Inductive-Load Switching Test Circuit



NOTES: A. Waveforms are monitored on an oscilloscope with the following characteristics: $t_r < 15$ ns, $R_{in} > 10 \Omega$, $C_{in} < 11.5$ pF.
 B. Resistors must be noninductive types.

Figure 4. Inductive-Load Switching Waveforms

PRODUCT INFORMATION

AUGUST 1978 - REVISED SEPTEMBER 2002
 Specifications are subject to change without notice.

TYPICAL CHARACTERISTICS




Figure 5.




Figure 6.




Figure 7.




Figure 8.

PRODUCT INFORMATION

TYPICAL CHARACTERISTICS




Figure 9.

MAXIMUM SAFE OPERATING REGIONS




Figure 10.

PRODUCT INFORMATION


AUGUST 1978 - REVISED SEPTEMBER 2002
 Specifications are subject to change without notice.

MECHANICAL DATA

SOT-93

3-pin plastic flange-mount package

This single-in-line package consists of a circuit mounted on a lead frame and encapsulated within a plastic compound. The compound will withstand soldering temperature with no deformation, and circuit performance characteristics will remain stable when operated in high humidity conditions. Leads require no additional cleaning or processing when used in soldered assembly.



NOTE A: The centre pin is in electrical contact with the mounting tab.

MDXXAW

PRODUCT INFORMATION

AUGUST 1978 - REVISED SEPTEMBER 2002
Specifications are subject to change without notice.