

- **2.5-V Virtual Ground for 5-V/GND Analog Systems**
- **High Output-Current Capability Sink or Source . . . 20 mA Typ**
- **Micropower Operation . . . 170 μ A Typ**
- **Excellent Regulation Characteristics**
 - **Output Regulation**
 -45μ V Typ at $I_O = 0$ to -10 mA
 $+15 \mu$ V Typ at $I_O = 0$ to $+10$ mA
 - **Input Regulation** = 1.5μ V/V Typ
- **Low-Impedance Output . . . 0.0075 Ω Typ**
- **Macromodel Included**


description

In signal-conditioning applications using a single power source, a reference voltage is required for termination of all signal grounds. To accomplish this, engineers have typically used solutions consisting of resistors, capacitors, operational amplifiers, and voltage references. Texas Instruments has eliminated all of those components with one easy-to-use 3-terminal device. That device is the TLE2425 precision virtual ground.

Use of the TLE2425 over other typical circuit solutions gives the designer increased dynamic signal range, improved signal-to-noise ratio, lower distortion, improved signal accuracy, and easier interfacing to ADCs and DACs. These benefits are the result of combining a precision micropower voltage reference and a high-performance precision operational amplifier in a single silicon chip. It is the precision and performance of these two circuit functions together that yield such dramatic system-level performance.

The TLE2425 improves input regulation as well as output regulation and, in addition, reduces output impedance and power dissipation in a majority of virtual-ground-generation circuits. Both input regulation and load regulation exceed 12 bits of accuracy on a single 5-V system. Signal-conditioning front ends of data acquisition systems that push 12 bits and beyond can use the TLE2425 to eliminate a major source of system error.

OUTPUT REGULATION



AVAILABLE OPTIONS

TA	SMALL OUTLINE (D)	PLASTIC TO-226AA (LP)
0°C to 70°C	TLE2425CD	TLE2425CD
-40°C to 85°C	TLE2425ID	TLE2425ID
-55°C to 125°C	TLE2425MD	—

† The D package is available taped and reeled. Add R suffix to the device type (e.g., TLE2425CDR).




Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

TLE2425

PRECISION VIRTUAL GROUND

SLOS065D – MARCH 1991 – REVISED APRIL 2002



NC – No internal connection

absolute maximum ratings over operating free-air temperature range (unless otherwise noted)[†]

Continuous input voltage, V_I	40 V
Output current, I_O	± 80 mA
Duration of short-circuit current at (or below) 25°C (see Note 1)	unlimited
Continuous total power dissipation	See Dissipation Rating Table
Operating free-air temperature range, T_A :	
C-suffix	0°C to 70°C
I-suffix	-40°C to 85°C
M-suffix	-55°C to 125°C
Storage temperature range, T_{stg}	-65°C to 150°C
Lead temperature 1,6 mm (1/16 inch) from case for 10 seconds: D package	260°C
Lead temperature 1,6 mm (1/16 inch) from case for 60 seconds: JG or LP package	300°C

[†] Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

NOTE 1: The output may be shorted to either supply. Temperature and/or supply voltages must be limited to ensure that the maximum dissipation rating is not exceeded.

DISSIPATION RATING TABLE

PACKAGE	$T_A \leq 25^\circ\text{C}$ POWER RATING	DERATING FACTOR ABOVE $T_A = 25^\circ\text{C}$	$T_A = 70^\circ\text{C}$		$T_A = 85^\circ\text{C}$		$T_A = 125^\circ\text{C}$	
			POWER RATING	POWER RATING	POWER RATING	POWER RATING	POWER RATING	POWER RATING
D	725 mV	5.8 mW/°C	464 mW	377 mW	145 mW			
JG	1050 mV	8.4 mW/°C	672 mW	546 mW	210 mW			
LP	775 mV	6.2 mW/°C	496 mW	403 mW	155 mW			

recommended operating conditions

	C-SUFFIX		I-SUFFIX		M-SUFFIX		UNIT
	MIN	MAX	MIN	MAX	MIN	MAX	
Input voltage, V_I	4	40	4	40	4	40	V
Operating free-air temperature, T_A	0	70	-40	85	-55	125	°C

electrical characteristics at specified free-air temperature, $V_I = 5 \text{ V}$, $I_O = 0$ (unless otherwise noted)

PARAMETER	TEST CONDITIONS	T_A^{\dagger}	TLE2425C			UNIT	
			MIN	TYP	MAX		
Output voltage		25°C	2.48	2.5	2.52	V	
		Full range	2.47		2.53		
Temperature coefficient of output voltage		25°C		20		ppm/°C	
Bias current	$I_O = 0$	25°C		170	250	μA	
		Full range			250		
Input voltage regulation	$V_I = 4.5 \text{ V to } 5.5 \text{ V}$		25°C	1.5	20	μV	
			Full range		25		
	$V_I = 4 \text{ V to } 40 \text{ V}$		25°C	1.5	20	$\mu\text{V/V}$	
			Full range		25		
Ripple rejection	$f = 120 \text{ Hz}$, $\Delta V_{I(PP)} = 1 \text{ V}$	25°C		80		dB	
Output voltage regulation (source current) [‡]	$I_O = 0 \text{ to } -10 \text{ mA}$		25°C	-160	-45	160	μV
			Full range	-250		250	
	$I_O = 0 \text{ to } -20 \text{ mA}$		25°C	-450	-150	450	
Output voltage regulation (sink current) [‡]	$I_O = 0 \text{ to } 10 \text{ mA}$		25°C	-160	15	160	μV
			Full range	-250		250	
	$I_O = 0 \text{ to } 20 \text{ mA}$		25°C	-235	65	235	
Long-term drift of output voltage	$\Delta t = 1000 \text{ h}$, Noncumulative	25°C		15		ppm	
Output impedance		25°C		7.5	22.5	$\text{m}\Omega$	
Short-circuit output current (sink current)	$V_O = 5 \text{ V}$	25°C		30	55	mA	
Short-circuit output current (source current)	$V_O = 0$			-30	-50		
Output noise voltage, rms	$f = 10 \text{ Hz to } 10 \text{ kHz}$	25°C		100		μV	
Output voltage response to output current step	V_O to 0.1%, $I_O = \pm 10 \text{ mA}$	25°C		110		μs	
	$C_L = 0$			115			
	$C_L = 100 \text{ pF}$			180			
	V_O to 0.01%, $I_O = \pm 10 \text{ mA}$			180			
Output voltage response to input voltage step	$V_I = 4.5 \text{ to } 5.5 \text{ V}$, V_O to 0.1%	25°C		12		μs	
	$V_I = 4.5 \text{ to } 5.5 \text{ V}$, V_O to 0.01%			30			
Output voltage turn-on response	$V_I = 0 \text{ to } 5 \text{ V}$, V_O to 0.1%	25°C		125		μs	
	$V_I = 0 \text{ to } 5 \text{ V}$, V_O to 0.01%			210			

[†] Full range is 0°C to 70°C.

[‡] The listed values are not production tested.

TLE2425 PRECISION VIRTUAL GROUND

SLOS065D – MARCH 1991 – REVISED APRIL 2002

electrical characteristics at specified free-air temperature, $V_I = 5 \text{ V}$, $I_O = 0$ (unless otherwise noted)

PARAMETER	TEST CONDITIONS	T_A^\dagger	TLE2425I			UNIT
			MIN	TYP	MAX	
Output voltage		25°C	2.48	2.5	2.52	V
		Full range	2.47		2.53	
Temperature coefficient of output voltage		25°C		20		ppm/°C
Bias current	$I_O = 0$	25°C		170	250	μA
		Full range			250	
Input voltage regulation	$V_I = 4.5 \text{ V to } 5.5 \text{ V}$	25°C		1.5	20	μV
		Full range			75	
	$V_I = 4 \text{ V to } 40 \text{ V}$	25°C		1.5	20	$\mu\text{V/V}$
		Full range			75	
Ripple rejection	$f = 120 \text{ Hz}$, $\Delta V_{I(\text{PP})} = 1 \text{ V}$	25°C		80		dB
Output voltage regulation (source current) ‡	$I_O = 0 \text{ to } -10 \text{ mA}$	25°C	-160	-45	160	μV
		Full range	-250		250	
	$I_O = 0 \text{ to } -20 \text{ mA}$	25°C	-450	-150	450	
Output voltage regulation (sink current) ‡	$I_O = 0 \text{ to } 8 \text{ mA}$	25°C	-160	15	160	μV
		Full range	-250		250	
	$I_O = 0 \text{ to } 20 \text{ mA}$	25°C	-235	65	235	
Long-term drift of output voltage	$\Delta t = 1000 \text{ h}$, Noncumulative	25°C		15		ppm
Output impedance		25°C		7.5	22.5	$\text{m}\Omega$
Short-circuit output current (sink current)	$V_O = 5 \text{ V}$	25°C	30	55		mA
Short-circuit output current (source current)	$V_O = 0$		-30	-50		
Output noise voltage, rms	$f = 10 \text{ Hz to } 10 \text{ kHz}$	25°C		100		μV
Output voltage response to output current step	$V_O \text{ to } 0.1\%$, $I_O = \pm 10 \text{ mA}$	$C_L = 0$		110		μs
				115		
	$V_O \text{ to } 0.01\%$, $I_O = \pm 10 \text{ mA}$	$C_L = 0$		180		
		$C_L = 100 \text{ pF}$		180		
Output voltage response to input voltage step	$V_I = 4.5 \text{ to } 5.5 \text{ V}$, $V_O \text{ to } 0.1\%$	25°C		12		μs
	$V_I = 4.5 \text{ to } 5.5 \text{ V}$, $V_O \text{ to } 0.01\%$			30		
Output voltage turn-on response	$V_I = 0 \text{ to } 5 \text{ V}$, $V_O \text{ to } 0.1\%$	25°C		125		μs
	$V_I = 0 \text{ to } 5 \text{ V}$, $V_O \text{ to } 0.01\%$			210		

† Full range is -40°C to 85°C .

‡ The listed values are not production tested.



POST OFFICE BOX 655303 • DALLAS, TEXAS 75265
POST OFFICE BOX 1443 • HOUSTON, TEXAS 77251-1443

electrical characteristics at specified free-air temperature, $V_I = 5 \text{ V}$, $I_O = 0$ (unless otherwise noted)

PARAMETER	TEST CONDITIONS	T_A^\dagger	TLE2425M			UNIT	
			MIN	TYP	MAX		
Output voltage		25°C	2.48	2.5	2.52	V	
		Full range	2.47		2.53		
Temperature coefficient of output voltage		25°C		20		ppm/°C	
Bias current	$I_O = 0$	25°C		170	250	μA	
		Full range			250		
Input voltage regulation	$V_I = 4.5 \text{ V to } 5.5 \text{ V}$		25°C	1.5	20	μV	
			Full range		100		
	$V_I = 4.5 \text{ V to } 40 \text{ V}$		25°C	1.5	20	$\mu\text{V/V}$	
			Full range		100		
Ripple rejection	$f = 120 \text{ Hz}$, $\Delta V_{I(PP)} = 1 \text{ V}$	25°C		80		dB	
Output voltage regulation (source current)‡	$I_O = 0 \text{ to } -10 \text{ mA}$		25°C	-160	-45	160	μV
			Full range	-250		250	
	$I_O = 0 \text{ to } -20 \text{ mA}$		25°C	-450	-150	450	
Output voltage regulation (sink current)‡	$I_O = 0 \text{ to } 3 \text{ mA}$		25°C	-160	15	160	μV
			Full range	-250		250	
	$I_O = 0 \text{ to } 20 \text{ mA}$		25°C	-235	65	235	
Long-term drift of output voltage	$\Delta t = 1000 \text{ h}$, Noncumulative	25°C		15		ppm	
Output impedance		25°C		7.5	22.5	$\text{m}\Omega$	
Short-circuit output current (sink current)	$V_O = 5 \text{ V}$	25°C		30	55	mA	
Short-circuit output current (source current)	$V_O = 0$			-30	-50		
Output noise voltage, rms	$f = 10 \text{ Hz to } 10 \text{ kHz}$	25°C		100		μV	
Output voltage response to output current step	V_O to 0.1%, $I_O = \pm 10 \text{ mA}$	25°C		110		μs	
	$C_L = 0$			115			
	$C_L = 100 \text{ pF}$			180			
	V_O to 0.01%, $I_O = \pm 10 \text{ mA}$			180			
Output voltage response to input voltage step	$V_I = 4.5 \text{ to } 5.5 \text{ V}$, V_O to 0.1%	25°C		12		μs	
	$V_I = 4.5 \text{ to } 5.5 \text{ V}$, V_O to 0.01%			30			
Output voltage turn-on response	$V_I = 0 \text{ to } 5 \text{ V}$, V_O to 0.1%	25°C		125		μs	
	$V_I = 0 \text{ to } 5 \text{ V}$, V_O to 0.01%			210			

† Full range is -55°C to 125°C .

‡ The listed values are not production tested.

TLE2425

PRECISION VIRTUAL GROUND

SLOS065D – MARCH 1991 – REVISED APRIL 2002

TYPICAL CHARACTERISTICS

Table Of Graphs

		FIGURE
Output voltage	Distribution	1
	vs Free-air temperature	2
Output voltage hysteresis	vs Free-air temperature	3
	vs Input voltage	4
Input bias current		5
	6	
Input voltage regulation		7
Ripple rejection	vs Frequency	8
Output voltage regulation		9
Output impedance	vs Frequency	10
Short-circuit output current	vs Free-air temperature	11
Spectral noise voltage density	vs Frequency	12
Wide-band noise voltage	vs Frequency	13
Output voltage change with current step	vs Time	14
Output voltage change with voltage step	vs Time	15
Output voltage power-up response	vs Time	16
Output current	vs Load capacitance	

TYPICAL CHARACTERISTICS[†]




Figure 1




Figure 2




Figure 3




Figure 4

[†] Data at high and low temperatures are applicable within rated operating free-air temperature ranges of the various devices.

TLE2425

PRECISION VIRTUAL GROUND

SLOS065D – MARCH 1991 – REVISED APRIL 2002

TYPICAL CHARACTERISTICS†

INPUT BIAS CURRENT
VS
FREE-AIR TEMPERATURE




Figure 5

INPUT VOLTAGE REGULATION




Figure 6

RIPPLE REJECTION
VS
FREQUENCY




Figure 7

OUTPUT VOLTAGE REGULATION




Figure 8

† Data at high and low temperatures are applicable within rated operating free-air temperature ranges of the various devices.



POST OFFICE BOX 655303 • DALLAS, TEXAS 75265
POST OFFICE BOX 1443 • HOUSTON, TEXAS 77251-1443

TYPICAL CHARACTERISTICS




Figure 9




Figure 10




Figure 11




Figure 12

TLE2425

PRECISION VIRTUAL GROUND

SLOS065D – MARCH 1991 – REVISED APRIL 2002

TYPICAL CHARACTERISTICS




Figure 13




Figure 14




Figure 15




Figure 16

macromodel information

```

* TLE2425 OPERATIONAL AMPLIFIER "MACROMODEL" SUBCIRCUIT
* CREATED USING PARTS RELEASE 4.03 ON 08/21/90 AT 13:51
* REV (N/A)      SUPPLY VOLTAGE: 5 V
* CONNECTIONS: INPUT
*           | COMMON
*           | OUTPUT
* .SUBCKT TLE2425 3 4 5
*
```

```

* OPAMP SECTION
C1    11 12 21.66E-12
C2    6 7 30.00E-12
C3    87 0 10.64E-9
CPSR  85 86 15.9E-9
DCM+  81 82 DX
DCM-  83 81 DX
DC    5 53 DX
DE    54 5 DX
DLN   92 90 DX
DLP   90 91 DX
DP    4 3 DX
ECMR  84 99 (2,99) 1
EGND  99 0 POLY(2) (3,0) (4,0) 0 .5 .5
EPSR  85 0 POLY(1) (3,4) -16.22E-6 3.24E-6
ENSE  89 2 POLY(1) (88,0) 120E-6 1
FB    7 99 POLY(6) VB VC VE VLP VLNVPSR O 74.8E6 -10E6 10E6 10E6
+ -10E6 74E6
GA    6 0 11 12 320.4E-6
GCM   0 6 10 99 1.013E-9
GPSR  85 86 (85,86) 100E-6
GRC1  4 11 (4,11) 3.204E-4
GRC2  4 12 (4,12) 3.204E-4
GRE1  13 10 (13,10) 1.038E-3
GRE2  14 10 (14,10) 1.038E-3
HLIM  90 0 VLIM 1K
HCMR  80 1 POLY(2) VCM+ VCM- 0 1E2 1E2
IRP   3 4 146E-6
IEE   3 10 DC 24.05E-6
IIO   2 0 .2E-9
I1    88 0 1E-21
Q1    11 89 13 QX
Q2    12 80 14 QX
R2    6 9 100.0E3
RCM   84 81 1K
REE   10 99 8.316E6
RN1   87 0 2.55E8
RN2   87 88 11.67E3

```



TLE2425

PRECISION VIRTUAL GROUND

SLOS065D – MARCH 1991 – REVISED APRIL 2002

macromodel information (continued)


```
RO1      8  5   63
RO2      7  99  62
VCM+    82 99  1.0
VCM-    83 99 -2.3
VB       9  0   DC  0
VC       3  53  DC 1.400
VE       54  4   DC 1.400
VLIM     7  8   DC  0
VLP      91  0   DC 30
VLN      0  92  DC 30
VPSR     0  86  DC  0
RFB      5  2   1K
RIN      30  1   1K
RCOM     34  4   .1
*REGULATOR SECTION
RG1      30  0   20MEG
RG2      30  31  .2
RG3      31  35  400K
RG4      35  34  411K
RG5      31  36  25MEG
HREG     31  32  POLY(2)  VPSET VNSET 0  1E2 1E2
VREG     32  33  DC 0V
EREG     33  34  POLY(1)  (36,34)  1.23 1
VADJ     36  34  1.27V
HPSET    37  0   VREG  1.030E3
VPSET    38  0   DC 20V
HNSET    39  0   VREG  6.11E5
VNSET    40  0   DC -20V
DSUB     4  34  DX
DPOS     37  38  DX
DNNEG    40  39  DX
.MODEL DX D(IS=800.0E-18)
.MODEL QX PNP(IS=800.0E-18 BF=480)
.ENDS
```

MECHANICAL INFORMATION

D (R-PDSO-G**)

PLASTIC SMALL-OUTLINE PACKAGE

14 PIN SHOWN



- NOTES: A. All linear dimensions are in inches (millimeters).
 B. This drawing is subject to change without notice.
 C. Body dimensions do not include mold flash or protrusion, not to exceed 0.006 (0,15).
 D. Falls within JEDEC MS-012


TLE2425 PRECISION VIRTUAL GROUND

SLOS065D – MARCH 1991 – REVISED APRIL 2002

MECHANICAL INFORMATION

JG (R-GDIP-T8)

CERAMIC DUAL-IN-LINE PACKAGE




- NOTES:
- A. All linear dimensions are in inches (millimeters).
 - B. This drawing is subject to change without notice.
 - C. This package can be hermetically sealed with a ceramic lid using glass frit.
 - D. Index point is provided on cap for terminal identification only on press ceramic glass frit seal only.
 - E. Falls within MIL-STD-1835 GDIP1-T8

MECHANICAL INFORMATION

LP (O-PBCY-W3)

PLASTIC CYLINDRICAL PACKAGE



- NOTES:
- All linear dimensions are in inches (millimeters).
 - This drawing is subject to change without notice.
 - Lead dimensions are not controlled within this area.
 - Falls within JEDEC TO-226AA (TO-226AA replaces TO-92)

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Mailing Address:

Texas Instruments
Post Office Box 655303
Dallas, Texas 75265