

**SOT23 NPN SILICON PLANAR
MEDIUM POWER TRANSISTOR**

BC817

ISSUE 5 – MARCH 2001




PART MARKING DETAILS

BC81716 – 6AZ

BC81725 – 6BZ

BC81740 – 6CZ

COMPLEMENTARY TYPE – BC807



SOT23

ABSOLUTE MAXIMUM RATINGS.

PARAMETER	SYMBOL	VALUE	UNIT
Collector-Base Voltage	V_{CBO}	50	V
Collector-Emitter Voltage	V_{CEO}	45	V
Emitter-Base Voltage	V_{EBO}	5	V
Peak Pulse Current	I_{CM}	1	A
Continuous Collector Current	I_C	500	mA
Base Current	I_B	100	mA
Peak Base Current	I_{BM}	200	mA
Power Dissipation at $T_{amb}=25^\circ\text{C}$	P_{tot}	330	mW
Operating and Storage Temperature Range	$T_j:T_{stg}$	-55 to +150	°C

ELECTRICAL CHARACTERISTICS (at $T_{amb} = 25^\circ\text{C}$ unless otherwise stated).

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	CONDITIONS.
Collector Cut-Off Current	I_{CBO}			0.1 5	μA	$V_{CB}=20\text{V}, I_E=0$ $V_{CB}=20\text{V}, I_E=0, T_{amb}=150^\circ\text{C}$
Emitter Cut-Off Current	I_{EBO}			10	μA	$V_{EB}=5\text{V}, I_C=0$
Collector-Emitter Saturation Voltage	$V_{CE(\text{sat})}$			700	mV	$I_C=500\text{mA}, I_B=50\text{mA}^*$
Base-Emitter Saturation Voltage	$V_{BE(\text{on})}$			1.2	V	$I_C=500\text{mA}, V_{CE}=1\text{V}^*$
Static Forward Current Transfer Ratio	h_{FE}					
BC81716		100		250		$I_C=100\text{mA}, V_{CE}=1\text{V}^*$
BC81725		160		400		$I_C=100\text{mA}, V_{CE}=1\text{V}^*$
BC81740		250		600		$I_C=100\text{mA}, V_{CE}=1\text{V}^*$
All bands		40				$I_C=500\text{mA}, V_{CE}=1\text{V}^*$
Transition Frequency	f_T		200		MHz	$I_C=10\text{mA}, V_{CE}=5\text{V}$ $f=35\text{MHz}$
Output Capacitance	C_{obo}		5.0		pF	$V_{CB}=10\text{V}, f=1\text{MHz}$

*Measured under pulsed conditions.

 **ZETEX**