

3 Amp. Glass Passivated Ultrafast Recovery Rectifier

Dimensions in mm. Mounting instructions <ol style="list-style-type: none"> Min. distance from body to soldering point, 4 mm. Max. solder temperature, 350 °C. Max. soldering time, 3.5 sec. Do not bend lead at a point closer than 3 mm. to the body. 	DO-201AD (Plastic) Voltage 50 to 1000 V. Current 3 A at 55 °C.
---	---

Maximum Ratings, according to IEC publication No. 134

		FUF5400	FUF5401	FUF5402	FUF5404	FUF5406	FUF5407	FUF5408
V_{RRM}	Peak Recurrent reverse voltage (V)	50	100	200	400	600	800	1000
V_{RMS}	Maximum RMS voltage	35	70	140	280	420	560	700
V_{DC}	Maximum DC blocking voltage	50	100	200	400	600	800	1000
$I_{F(AV)}$	Forward current at Tamb = 55 °C							3 A
I_{FRM}	Recurrent peak forward surge current							30 A
I_{FSM}	8.3 ms. peak forward surge current (Jedec Method)							150 A
t_{rr}	Max. reverse recovery time from $I_F = 0.5 \text{ A}$; $I_R = 1 \text{ A}$; $I_{RR} = 0.25 \text{ A}$				50 ns			75 ns
C_j	Typical Junction Capacitance at 1 MHz and reverse voltaje of $4V_{DC}$					45 pF		
T_j	Operating temperature range							- 65 to + 150 °C
T_{stg}	Storage temperature range							- 65 to + 150 °C
E_{RSM}	Maximum non repetitive peak reverse avalanche energy. $I_R = 1 \text{ A}$; $T_j = 25 \text{ °C}$							20 mJ

Electrical Characteristics at Tamb = 25 °C

V_F	Max. forward voltage drop at $I_F = 3 \text{ A}$	1.3 V	1.7 V
I_R	Max. reverse current at V_{RRM} at 25 °C		5 μA
R_{thj-a}	Max. thermal resistance (l = 10 mm.)		30 °C/W

Rating And Characteristic Curves

