


3 Amp. Glass Passivated Avalanche Ultrafast Recovery Rectifier

<p>Dimensions in mm.</p>  <p>DO-201AD (Plastic)</p>	<p>Voltage 50 to 600 V.</p> <p>Current 3 A at 55 °C.</p> 
<p>Mounting instructions</p> <ol style="list-style-type: none"> Min. distance from body to soldering point, 4 mm. Max. solder temperature, 350 °C. Max. soldering time, 3.5 sec. Do not bend lead at a point closer than 3 mm. to the body. 	<ul style="list-style-type: none"> • Glass Passivated Junction • High current capability • The plastic material carries U/L recognition 94 V-0 • Terminals: Axial Leads • Polarity: Color band denotes cathode

Maximum Ratings, according to IEC publication No. 134

		EGP30A	EGP30B	EGP30D	EGP30F	EGP30G	EGP30J
V_{RRM}	Peak Recurrent reverse voltage (V)	50	100	200	300	400	600
V_{RMS}	Maximum RMS voltage	35	70	140	210	280	420
V_{DC}	Maximum DC blocking voltage	50	100	200	300	400	600
$I_{F(AV)}$	Forward current at Tamb = 55 °C						3 A
I_{FRM}	Recurrent peak forward current						30 A
I_{FSM}	8.3 ms. peak forward surge current (Jedec Method)						125 A
t_{rr}	Max. reverse recovery time from $I_F = 0.5$ A ; $I_R = 1$ A ; $I_{RR} = 0.25$ A						50 ns
C_j	Typical Junction Capacitance at 1 MHz and reverse voltage of 4 V_{DC}		90 pF				45 pF
T_j	Operating temperature range						- 65 to + 150 °C
T_{stg}	Storage temperature range						- 65 to + 150 °C
E_{RSM}	Maximum non repetitive peak reverse avalanche energy. $I_R = 1$ A ; $T_j = 25$ °C						20 mJ

Electrical Characteristics at Tamb = 25 °C

V_F	Max. forward voltage drop at $I_F = 3$ A	0.95 V	1.25 V
I_R	Max. reverse current at V_{RRM} at 25 °C at 150 °C	5 μ A 50 μ A	
R_{thj-a}	Max. thermal resistance (l = 10 mm.)	30 °C/W	

Rating And Characteristic Curves

