

2.5V/3.3V SiGe 1:2 Differential Clock Driver with RSECL* Outputs

*Reduced Swing ECL

The NBSG11 is a 1-to-2 differential fanout buffer, optimized for low skew and ultra-low JITTER.

Inputs incorporate internal $50\ \Omega$ termination resistors and accept NECL (Negative ECL), PECL (Positive ECL), CML, LVCMOS, LVTTL, or LVDS. Outputs are RSECL (Reduced Swing ECL), 400 mV.


- Maximum Input Clock Frequency up to 12 GHz Typical
- Maximum Input Data Rate up to 12 Gb/s Typical
- 30 ps Typical Rise and Fall Times
- 125 ps Typical Propagation Delay
- RSPECL Output with Operating Range: $V_{CC} = 2.375\text{ V}$ to 3.465 V with $V_{EE} = 0\text{ V}$
- RSNECL Output with RSNECL or NECL Inputs with Operating Range: $V_{CC} = 0\text{ V}$ with $V_{EE} = -2.375\text{ V}$ to -3.465 V
- RSECL Output Level (400 mV Peak-to-Peak Output), Differential Output Only
- 50 Ω Internal Input Termination Resistors
- Compatible with Existing 2.5 V/3.3 V LVEP, EP, and LVEL Devices




ON Semiconductor®

<http://onsemi.com>

MARKING DIAGRAM*




FCCGA-16
BA SUFFIX
CASE 489



SG
11
LYW



QFN-16
MN SUFFIX
CASE 485G



SG11
ALYW

A = Assembly Location

L = Wafer Lot

Y = Year

W = Work Week

*For further details, refer to Application Note AND8002/D

ORDERING INFORMATION

Device	Package	Shipping
NBSG11BA	4x4 mm FCCGA-16	100 Units / Tray
NBSG11BAR2	4x4 mm FCCGA-16	500 / Tape & Reel
NBSG11MN	3x3 mm QFN-16	123 Units / Rail
NBSG11MNR2	3x3 mm QFN-16	3000 / Tape & Reel

Board	Description
NBSG11BAEVB	NBSG11BA Evaluation Board

NBSG11




Figure 1. BGA-16 Pinout (Top View)




Figure 2. QFN-16 Pinout (Top View)

Table 1. Pin Description

Pin		Name	I/O	Description
BGA	QFN			
D1	1	VTCLK	-	Internal 50 Ω Termination Pin. See Table 2.
C1	2	CLK	ECL, CML, LVCMS, LVDS, LVTTL Input	Inverted Differential Input. Internal 75 kΩ to V _{EE} and 36.5 kΩ to V _{CC} .
B1	3	CLK	ECL, CML, LVCMS, LVDS, LVTTL Input	Noninverted Differential Input. Internal 75 kΩ to V _{EE} .
A1	4	VTCLK	-	Internal 50 Ω Termination Pin. See Table 2.
B2,C2	5,16	V _{EE}	-	Negative Supply Voltage
A2,A3,D2, D3	6,7,14,15	NC	-	No Connect
B3,C3	8,13	V _{CC}	-	Positive Supply Voltage
A4	9	Q1	RSECL Output	Inverted Differential Output 1. Typically Terminated with 50 Ω to V _{TT} = V _{CC} - 2 V
B4	10	Q1	RSECL Output	Noninverted Differential Output 1. Typically Terminated with 50 Ω to V _{TT} = V _{CC} - 2 V
C4	11	Q0	RSECL Output	Inverted Differential output 0. Typically Terminated with 50 Ω to V _{TT} = V _{CC} - 2 V
D4	12	Q0	RSECL Output	Noninverted Differential Output 0. Typically Terminated with 50 Ω to V _{TT} = V _{CC} - 2 V
N/A	-	EP	-	Exposed Pad (Note 2)

1. The NC pins are electrically connected to the die and must be left open.
2. All V_{CC} and V_{EE} pins must be externally connected to Power Supply to guarantee proper operation. The thermally exposed pad on package bottom (see case drawing) must be attached to a heat-sinking conduit.
3. In the differential configuration when the input termination pins (VTCLK, VTCLK) are connected to a common termination voltage, and if no signal is applied then the device will be susceptible to self-oscillation.




Figure 3. Logic Diagram

Table 2. Interfacing Options

INTERFACING OPTIONS	CONNECTIONS
CML	Connect VTCLK and $\overline{\text{VTCLK}}$ to V_{CC}
LVDS	Connect VTCLK and $\overline{\text{VTCLK}}$ together
AC-COUPLED	Bias VTCLK and $\overline{\text{VTCLK}}$ Inputs within (VIHCMR) Common Mode Range
RSECL, PECL, NECL	Standard ECL Termination Techniques
LVTTL, LVCMOS	An external voltage should be applied to the unused complementary differential input. Nominal voltage is 1.5 V for LVTTL and $V_{CC}/2$ for LVCMOS inputs.

Table 3. ATTRIBUTES

Characteristics	Value
Internal Input Pulldown Resistor (CLK, $\overline{\text{CLK}}$)	75 kΩ
Internal Input Pullup Resistor ($\overline{\text{CLK}}$)	36.5 kΩ
ESD Protection	Human Body Model Machine Model
	> 2 kV > 100 V
Moisture Sensitivity (Note 4)	FCBGA-16 QFN-16
Flammability Rating	Oxygen Index: 28 to 34
Transistor Count	Level 3 Level 1
Meets or exceeds JEDEC Spec EIA/JESD78 IC Latchup Test	UL 94 V-0 @ 0.125 in

4. For additional information, see Application Note AND8003/D.

Table 4. MAXIMUM RATINGS (Note 5)

Symbol	Parameter	Condition 1	Condition 2	Rating	Units
V _{CC}	Positive Power Supply	V _{EE} = 0 V		3.6	V
V _{EE}	Negative Power Supply	V _{CC} = 0 V		-3.6	V
V _I	Positive Input Negative Input	V _{EE} = 0 V V _{CC} = 0 V	V _I ≤ V _{CC} V _I ≥ V _{EE}	3.6 -3.6	V V
V _{INPP}	Differential Input Voltage D - D̄	V _{CC} - V _{EE} ≥ 2.8 V V _{CC} - V _{EE} < 2.8 V		2.8 V _{CC} - V _{EE}	V V
I _{out}	Output Current	Continuous Surge		25 50	mA mA
T _A	Operating Temperature Range	16 FCBGA 16 QFN		-40 to +70 -40 to +85	°C
T _{stg}	Storage Temperature Range			-65 to +150	°C
θ _{JA}	Thermal Resistance (Junction-to-Ambient) (Note 6)	0 LFPM 500 LFPM 0 LFPM 500 LFPM	16 FCBGA 16 FCBGA 16 QFN 16 QFN	108 86 41.6 35.2	°C/W °C/W °C/W °C/W
θ _{JC}	Thermal Resistance (Junction-to-Case)	1S2P (Note 6) 2S2P (Note 7)	16 FCBGA 16 QFN	5.0 4.0	°C/W °C/W
T _{sol}	Wave Solder	< 15 Seconds		225	°C

5. Maximum Ratings are those values beyond which device damage may occur.

6. JEDEC standard multilayer board - 1S2P (1 signal, 2 power).

7. JEDEC standard multilayer board - 2S2P (2 signal, 2 power) with 8 filled thermal vias under exposed pad.

Table 5. DC CHARACTERISTICS, INPUT WITH RSPECL OUTPUT V_{CC} = 2.5 V; V_{EE} = 0 V (Note 8)

Symbol	Characteristic	-40 °C			25°C			70°C(BGA)/85°C(QFN)**			Unit
		Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	
I _{EE}	Negative Power Supply Current	45	60	75	45	60	75	45	60	75	mA
V _{OH}	Output HIGH Voltage (Note 9)	1450	1530	1575	1525	1565	1600	1550	1590	1625	mV
V _{OUTPP}	Output Amplitude Voltage	350	410	525	350	410	525	350	410	525	mV
V _{IH}	Input HIGH Voltage (Single-Ended) (Note 11)	V _{CC} -1435 mV	V _{CC} -1000 mV*	V _{CC}	V _{CC} -1435 mV	V _{CC} -1000 mV*	V _{CC}	V _{CC} -1435 mV	V _{CC} -1000 mV*	V _{CC}	V
V _{IL}	Input LOW Voltage (Single-Ended) (Note 12)	V _{IH} -2.5 V	V _{CC} -1400 mV*	V _{IH} -150 mV	V _{IH} -2.5 V	V _{CC} -1400 mV*	V _{IH} -150 mV	V _{IH} -2.5 V	V _{CC} -1400 mV*	V _{IH} -150 mV	V
V _{IHCMR}	Input HIGH Voltage Common Mode Range (Differential Configuration) (Note 10)	1.2		2.5	1.2		2.5	1.2		2.5	V
R _{TIN}	Internal Input Termination Resistor	45	50	55	45	50	55	45	50	55	Ω
I _{IH}	Input HIGH Current (@ V _{IH} , V _{IHM})		80	150		80	150		80	150	μA
I _{IL}	Input LOW Current (@ V _{IL} , V _{ILM})		25	100		25	100		25	100	μA

NOTE: SiGe circuits are designed to meet the DC specifications shown in the above table after thermal equilibrium has been established. The circuit is in a test socket or mounted on a printed circuit board and transverse airflow greater than 500 lfpm is maintained.

8. Input and output parameters vary 1:1 with V_{CC}. V_{EE} can vary +0.125 V to -0.965 V.9. All loading with 50 Ω to V_{CC} - 2.0 V. V_{OH}/V_{OL} measured at V_{IH}/V_{IL}.10. V_{IHCMR} min varies 1:1 with V_{EE}, V_{IHCMR} max varies 1:1 with V_{CC}. The V_{IHCMR} range is referenced to the most positive side of the differential input signal.11. V_{IH} cannot exceed V_{CC}.12. V_{IL} always ≥ V_{EE}.

*Typicals used for testing purposes.

**The device packaged in FCBGA-16 have maximum temperature specification of 70°C and devices packaged in QFN-16 have maximum temperature specification of 85°C.

Table 6. DC CHARACTERISTICS, INPUT WITH RSPECL OUTPUT $V_{CC} = 3.3$ V; $V_{EE} = 0$ V (Note 13)

Symbol	Characteristic	-40 °C			25°C			70°C(BGA)/85°C(QFN)**			Unit
		Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	
I_{EE}	Negative Power Supply Current	45	60	75	45	60	75	45	60	75	mA
V_{OH}	Output HIGH Voltage (Note 14)	2250	2330	2375	2325	2365	2400	2350	2390	2425	mV
V_{OUTPP}	Output Amplitude Voltage	350	410	525	350	410	525	350	410	525	mV
V_{IH}	Input HIGH Voltage (Single-Ended) (Note 16)	$V_{CC}-1435$ mV	$V_{CC}-1000$ mV*	V_{CC}	$V_{CC}-1435$ mV	$V_{CC}-1000$ mV*	V_{CC}	$V_{CC}-1435$ mV	$V_{CC}-1000$ mV*	V_{CC}	V
V_{IL}	Input LOW Voltage (Single-Ended) (Note 17)	$V_{IH}-2.5$ V	$V_{CC}-1400$ mV*	$V_{IH}-150$ mV	$V_{IH}-2.5$ V	$V_{CC}-1400$ mV*	$V_{IH}-150$ mV	$V_{IH}-2.5$ V	$V_{CC}-1400$ mV*	$V_{IH}-150$ mV	V
V_{IHCMR}	Input HIGH Voltage Common Mode Range (Note 15) (Differential Configuration)	1.2		3.3	1.2		3.3	1.2		3.3	V
R_{TIN}	Internal Input Termination Resistor	45	50	55	45	50	55	45	50	55	Ω
I_{IH}	Input HIGH Current (@ V_{IH} , V_{IHMAX})		80	150		80	150		80	150	μ A
I_{IL}	Input LOW Current (@ V_{IL} , V_{ILMIN})		25	100		25	100		25	100	μ A

NOTE: SiGe Circuits are designed to meet the DC specifications shown in the above table after thermal equilibrium has been established. The circuit is in a test socket or mounted on a printed circuit board and transverse airflow greater than 500 lfpm is maintained.

13. Input and output parameters vary 1:1 with V_{CC} . V_{EE} can vary +0.925 V to -0.165 V.

14. All loading with 50Ω to V_{CC} - 2.0 V. V_{OH}/V_{OL} measured at V_{IH}/V_{IL} .

15. V_{IHCMR} min varies 1:1 with V_{EE} , V_{IHCMR} max varies 1:1 with V_{CC} . The V_{IHCMR} range is referenced to the most positive side of the differential input signal.

16. V_{IH} cannot exceed V_{CC} .

17. V_{IL} always $\geq V_{EE}$.

*Typicals used for testing purposes.

**The device packaged in FCBGA-16 have maximum temperature specification of 70°C and devices packaged in QFN-16 have maximum temperature specification of 85°C.

Table 7. DC CHARACTERISTICS, NECL OR RSNECL INPUT WITH NECL OUTPUTV_{CC} = 0 V; V_{EE} = -3.465 V to -2.375 V (Note 18)

Symbol	Characteristic	-40 °C			25°C			70°C(BGA)/85°C(QFN)**			Unit
		Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	
I _{EE}	Negative Power Supply Current	45	60	75	45	60	75	45	60	75	mA
V _{OH}	Output HIGH Voltage (Note 19)	-1050	-970	-925	-975	-935	-900	-950	-910	-875	mV
V _{OUTPP}	Output Amplitude Voltage	350	410	525	350	410	525	350	410	525	mV
V _{IH}	Input HIGH Voltage (Single-Ended) (Note 21)	V _{CC} -1435 mV	V _{CC} -1000 mV*	V _{CC}	V _{CC} -1435 mV	V _{CC} -1000 mV*	V _{CC}	V _{CC} -1435 mV	V _{CC} -1000 mV*	V _{CC}	V
V _{IL}	Input LOW Voltage (Single-Ended) (Note 22)	V _{IH} -2.5 V	V _{CC} -1400 mV*	V _{IH} -150 mV	V _{IH} -2.5 V	V _{CC} -1400 mV*	V _{IH} -150 mV	V _{IH} -2.5 V	V _{CC} -1400 mV*	V _{IH} -150 mV	V
V _{IHCMR}	Input HIGH Voltage Common Mode Range (Differential Configuration) (Note 20)	V _{EE} +1.2		0.0	V _{EE} +1.2		0.0	V _{EE} +1.2		0.0	V
R _{TIN}	Internal Input Termination Resistor	45	50	55	45	50	55	45	50	55	Ω
I _{IH}	Input HIGH Current (@ V _{IH} , V _{IHM})		80	150		80	150		80	150	μA
I _{IL}	Input LOW Current (@ V _{IL} , V _{ILM})		25	100		25	100		25	100	μA

NOTE: SiGe circuits are designed to meet the DC specifications shown in the above table after thermal equilibrium has been established. The circuit is in a test socket or mounted on a printed circuit board and transverse airflow greater than 500 l/fpm is maintained.

18. Input and output parameters vary 1:1 with V_{CC}.

19. All loading with 50 Ω to V_{CC} - 2.0 V. V_{OH}/V_{OL} measured at V_{IH}/V_{IL}.

20. V_{IHCMR} min varies 1:1 with V_{EE}, V_{IHCMR} max varies 1:1 with V_{CC}. The V_{IHCMR} range is referenced to the most positive side of the differential input signal.

21. V_{IH} cannot exceed V_{CC}.

22. V_{IL} always ≥ V_{EE}.

*Typicals used for testing purposes.

**The device packaged in FCBGA-16 have maximum temperature specification of 70°C and devices packaged in QFN-16 have maximum temperature specification of 85°C.

Table 8. AC CHARACTERISTICS for FCBGA-16V_{CC} = 0 V; V_{EE} = -3.465 V to -2.375 V or V_{CC} = 2.375 V to 3.465 V; V_{EE} = 0 V

Symbol	Characteristic	-40 °C			25°C			70°C			Unit
		Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	
f _{max}	Maximum Frequency (See Figure 4. f _{max} /JITTER) (Note 23)	10.709	12		10.709	12		10.709	12		GHz
t _{PLH} , t _{PHL}	Propagation Delay to Output Differential	90	125	160	90	125	160	90	125	160	ps
t _{SKew}	Duty Cycle Skew (Note 24) Within-Device Skew (Note 25) Device-to-Device Skew (Note 26)		3 6 25	15 15 50		3 6 25	15 15 50		3 6 25	15 15 50	ps
t _{JITTER}	RMS Random Clock Jitter f _{in} < 10 GHz Peak-to-Peak Data Dependent Jitter f _{in} < 10 Gb/s		0.2 TBD	1		0.2 TBD	1		0.2 TBD	1	ps
V _{INPP}	Input Voltage Swing/Sensitivity (Differential Configuration) (Note 27)	75		2600	75		2600	75		2600	mV
t _r , t _f	Output Rise/Fall Times (20% - 80%) @ 1 GHz	Q, Q̄	20	30	55	20	30	55	20	30	ps

23. Measured using a 500 mV source, 50% duty cycle clock source. All loading with 50 Ω to V_{CC}-2.0 V. For minimum f_{max} value of 10.709 GHz, output amplitude is approximately 200 mV (as shown in Figure 4, where output P-P spec is shown as a minimum/guarantee of around 150 mV). Input edge rates 40 ps (20% - 80%).

24. See Figure 5. t_{SKew} = |t_{PLH} - t_{PHL}| for a nominal 50% Differential Clock Input Waveform.

25. Within-Device skew is defined as identical transitions on similar paths through a device.

26. Device-to-device skew for identical transitions at identical V_{CC} levels.

27. V_{INPP} (MAX) cannot exceed V_{CC} - V_{EE}.

Table 9. AC CHARACTERISTICS for QFN-16 $V_{CC} = 0$ V; $V_{EE} = -3.465$ V to -2.375 V or $V_{CC} = 2.375$ V to 3.465 V; $V_{EE} = 0$ V

Symbol	Characteristic	-40 °C			25°C			85°C			Unit	
		Min	Typ	Max	Min	Typ	Max	Min	Typ	Max		
f_{max}	Maximum Frequency (See Figure 4. F_{max} /JITTER) (Note 28)	10.5	12		10.5	12		10.5	12		GHz	
t_{PLH}, t_{PHL}	Propagation Delay to Output Differential	90	125	160	90	125	160	90	125	160	ps	
t_{SKEW}	Duty Cycle Skew (Note 29) Within-Device Skew (Note 30) Device-to-Device Skew (Note 31)		3 6 25	15 15 50		3 6 25	15 15 50		3 6 25	15 15 50	ps	
t_{JITTER}	RMS Random Clock Jitter $f_{in} < 10$ GHz Peak-to-Peak Data Dependent Jitter $f_{in} < 10$ Gb/s		0.2 TBD	1		0.2 TBD	1		0.2 TBD	1	ps	
V_{INPP}	Input Voltage Swing/Sensitivity (Differential Configuration) (Note 32)	75		2600	75		2600	75		2600	mV	
t_r t_f	Output Rise/Fall Times (20% - 80%) @ 1 GHz	Q, \bar{Q}	15	30	55	20	30	55	20	30	55	ps

28. Measured using a 500 mV source, 50% duty cycle clock source. All loading with 50Ω to V_{CC} -2.0 V. For minimum f_{max} value of 10.5 GHz, output amplitude is approximately 200 mV (as shown in Figure 4, where output P-P spec is shown as a minimum/guarantee of around 150 mV). Input edge rates 40 ps (20% - 80%).

29. See Figure 5. $t_{SKEW} = |t_{PLH} - t_{PHL}|$ for a nominal 50% Differential Clock Input Waveform.

30. Within-Device skew is defined as identical transitions on similar paths through a device.

31. Device-to-device skew for identical transitions at identical V_{CC} levels.

32. V_{INPP} (MAX) cannot exceed $V_{CC} - V_{EE}$.




Figure 4. Output Voltage Amplitude (V_{OUTPP}) / RMS Jitter vs. Input Frequency (f_{in}) at Ambient Temperature (Typical)

NBSG11




Figure 5. AC Reference Measurement





Figure 6. Typical Termination for Output Driver and Device Evaluation
(Refer to Application Note AND8020 - Termination of ECL Logic Devices)

PACKAGE DIMENSIONS

FCBGA-16

BA SUFFIX

PLASTIC 4X4 (mm) BGA FLIP CHIP PACKAGE
CASE 489-01
ISSUE O




NOTES:

1. DIMENSIONS ARE IN MILLIMETERS.
2. INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M, 1994.
3. DIMENSION b IS MEASURED AT THE MAXIMUM SOLDER BALL DIAMETER, PARALLEL TO DATUM PLANE Z.
4. DATUM Z (SEATING PLANE) IS DEFINED BY THE SPHERICAL CROWNS OF THE SOLDER BALLS.
5. PARALLELISM MEASUREMENT SHALL EXCLUDE ANY EFFECT OF MARK ON TOP SURFACE OF PACKAGE.

DIM	MILLIMETERS	
	MIN	MAX
A	1.40	MAX
A1	0.25	0.35
A2	1.20	REF
b	0.30	0.50
D	4.00	BSC
E	4.00	BSC
e	1.00	BSC
S	0.50	BSC

PACKAGE DIMENSIONS

**16 PIN QFN
MN SUFFIX
CASE 485G-01
ISSUE O**



- NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
 2. CONTROLLING DIMENSION: MILLIMETERS.
 3. DIMENSION D APPLIES TO PLATED TERMINAL AND IS MEASURED BETWEEN 0.25 AND 0.30 MM FROM TERMINAL.
 4. COPLANARITY APPLIES TO THE EXPOSED PAD AS WELL AS THE TERMINALS.

DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	3.00	BSC	0.118	BSC
B	3.00	BSC	0.118	BSC
C	0.80	1.00	0.031	0.039
D	0.23	0.28	0.009	0.011
E	1.75	1.85	0.069	0.073
F	1.75	1.85	0.069	0.073
G	0.50	BSC	0.020	BSC
H	0.875	0.925	0.034	0.036
J	0.20	REF	0.008	REF
K	0.00	0.05	0.000	0.002
L	0.35	0.45	0.014	0.018
M	1.50	BSC	0.059	BSC
N	1.50	BSC	0.059	BSC
P	0.875	0.925	0.034	0.036
R	0.60	0.80	0.024	0.031

ON Semiconductor and  are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer.

PUBLICATION ORDERING INFORMATION

Literature Fulfillment:

Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada
Email: ONlit@hibbertco.com

N. American Technical Support: 800-282-9855 Toll Free USA/Canada

JAPAN: ON Semiconductor, Japan Customer Focus Center

2-9-1 Kamiimeguro, Meguro-ku, Tokyo, Japan 153-0051
Phone: 81-3-5773-3850

ON Semiconductor Website: <http://onsemi.com>

For additional information, please contact your local
Sales Representative.